

## VISTA-10P

### CONTROL PANEL



Honeywell's feature-rich VISTA-10P is the industry's most economical and versatile control panel and is ideally suited for a wide range of applications. The six-zone panel significantly reduces dealer training and service call costs thanks to user-friendly features that make operation easier than ever. VISTA-10P gives you the ability to send alarm signals and upload/download via an Internet Protocol (IP), improving the speed at which information can be delivered to and from the control panel. In addition, when used with an AlarmNet Internet or digital communicator, the VISTA-10P can be installed in premises without TELCO lines – guaranteeing communication independent of any home infrastructure. The VISTA-10P increases upsell opportunities through its expansion capabilities and flexibility.

## FEATURES

- IP alarm reporting and uploading/downloading capability for Internet and Intranet use via 7845i, 7845i-ENT, 7845GSMR or 7845i-GSM
- Six hardwired zones on board
- 16 wireless expansion zones totaling 22 protection zones
- Eight independent keyfob zones allow two wireless keys to be programmed without using any of the 22 zones
- 32 Event log
- 16 user codes
- One configurable zone type allows installers to create their own custom zone type
- Two on-board triggers
- Four output devices using a 4204 relay module
- Valuable End-User Features**
  - Flexible function keys allow single button arming
  - One programmable macro key
  - Viewable on system keypad display
    - Exit countdown
    - Time and date\*
    - Event log\*
  - Two schedules
    - Can activate relays on programmed times or on events
    - Latchkey reports to a pager
    - “User Access” time windows
- Chime by zone
- 4286 Phone Module allows system control from any touchtone phone
- Four output devices with multiple actions per device
  - Turn lights on when system disarms with a 4204 Relay
  - Flash same lights when system is in alarm using a 4204 Relay

\*with Alpha Keypad

# VISTA-10P

## CONTROL PANEL

### SPECIFICATIONS

---

#### Electrical

- Aux power 12VDC, 600mA max
- Seven hour standby at 400 mA aux load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0A max
- For UL installations, combined aux and alarm output cannot exceed 700mA

#### Output Control

- Supports multiple output devices, one 4204 and two triggers

#### Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus one configurable zone type
- Programmable swinger suppression

#### Expansion Devices

- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)

#### Accessories

- 7845i Internet Communicator
- 7845i-ENT Enterprise Internet Communicator
- 7845GSMR Dual-Path Digital Wireless Communicator
- 7845i-GSM Triple-Path Digital Communicator
- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to eight zones – 60mA, 5881ENM supports up to 16 zones
- 5881ENH supports up to 22 zones – 50mA
- 5883 Transceiver supports up to 26 zones – 80mA
- Supports Eagle 1225 and 1221 boards

#### Keypads

- 6160 Custom Alpha (required for programming) – 100mA
- 6160V Custom Alpha Voice – 100mA
- 6150 Fixed English LCD – 85mA/40mA
- 6150V Fixed English Voice LCD – 85mA/40mA
- 6150RF Fixed English RF LCD – 85mA/40mA
- 6148 Fixed English LCD – 70mA/30mA

#### Agency Listings

- UL Residential Fire, Burglary and CSFM
- ETL Residential Fire, Burglary

#### Smoke Detectors

- Supports four-wire smoke detectors

#### Communications

- 7845i Internet Communicator
- 7845i-ENT Enterprise Internet Communicator
- 7845GSMR Dual-Path Digital Wireless Communicator
- 7845i-GSM Triple-Path Digital Communicator
- Touchtone or pulse
- Formats supported
  - ADEMCO Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual - True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

### ORDERING

<b>VISTA-10P</b>	Control Panel
<b>VISTA-10PSIA</b>	Control Panel for CP-01 SIA certifications

#### Automation and Control Solutions

Honeywell Security & Communications  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747

www.honeywell.com

L/VISTA10P/D  
September 2008  
© 2008 Honeywell International Inc.

# Honeywell