

ALL PRODUCTS CATALOG

Standard Ball Valves

75 SERIES



Bronze padlockable ball valve; rated 600 psig CWP; stainless steel lever and nut optional. Automatic drain available. Sizes 1/4" to 2".

76 SERIES



Stainless steel standard ball valve; investment cast components. 2,000 CWP to 1", 1,000 CWP 1-1/2" to 3". Sizes: 1/4" to 3". 76-600 Series - Stainless steel 3-way diversion ball valve; 800 psig WOG, investment cast components.

76-300/400 SERIES



Stainless steel ball valve with double union ends; blow-out proof stem, all wetted metallic parts are 316 stainless steel. RPTFE seats and seals, adjustable packing gland and stainless steel lever and nut. Sizes 1/2" to 2".

76F-A SERIES



Economy stainless steel full port valve, 1000# CWP rating. Threaded ends, blowout proof stem, investment cast body, 316 SS components, including stainless handle. RPTFE seats and long life MPTFE packing. Sizes 1/4" to 2".

77 SERIES



Bronze full port ball valve with mounting pad; designed for easy actuator mounting. Sizes 1/4" through 2-1/2". Available in NPT and SAE threads. Also available with solder connections - no mounting pads.

77C/77CLF SERIES



Full port "Contractor Series" bronze ball valve with solid chrome-plated ball for superior flow characteristics. U.S. made cast bronze body and retainer. NPT and ANSI B16.18 solder end connections available. Sizes 1/4" to 2-1/2".



77W/77WLF SERIES



ApolloXpress™ ball valves are designed for direct mechanical connection to copper tubing in sizes 1/2"-2". The 77W complies with ANSI/NSF 61 Section 8 and is ideal for plumbing and heating systems. The press connections ensure easy installation with standard crimping tools. Rated 250 CWP, now with Leak Before Press™ feature.



89 SERIES



Carbon steel ball valve with threaded ends; 1500 and 2000 psig CWP; easy actuator mounting. Sizes 1/4" to 3". (Actuator Ready version: 89-ARX-64)

90 SERIES



Compact bronze uni-body ball valve that's UL listed at 400 psig CWP for fuel gases and flammable liquids. Also ideal for general purpose applications. Sizes 1/2" to 2".

92-100 SERIES



Compact bar stock steel unibody ball valve. Certified fire safe with graphite packing; RPTFE seats and seals, blowout-proof stem design. Sizes 1/4" to 2".