


INTERCEPTORS

FIG. 8925 SERIES SEDIMENT/OIL INTERCEPTOR


FUNCTION: Used in service stations, parking garages, car and truck washes and industrial plants where discharged water contains oily sediment and sludge. The sediment and sludge are collected in the sediment pan and removable bucket. The oily residue is trapped in the interceptor and can be skimmed off periodically.








Top View







H20 Ductile Iron Grate Detail··

NOTE: Interceptor shall be vented on outlet side per

local code requirements

NOTE: It is the responsibility of the installer to check all parts (internal and external) to verify they are in

their proper operating order and location.

**NOTE: When specifying H20 Ductile Iron Slotted Grate,

the length and width dimensions may vary when

using this Grate.

														ADD FOR:					
	SLUDGE CAP LBS		B OUTLET SIZE	r	D	_	_	G	u		l v	NO. OF 12" X 24" GRATES		AND OUT	EXT. (-E) UP TO 6"		FLANGE	FLANGE AND FLASHING CLAMP (-FC)	APPROX. Weight LBS.
NU.	UAP LDS	SIZE	SIZE	U	ע		Г	u	п	J	N	UNATES	COATED	(-Aniu)	U	UVEN U	(-1)	CLAIVIF (-FC)	LDS.
8925-12	12	02"	02"	18"	13"	10 1/2"	17 1/2"	12 1/2"	12 1/2"	9"	6"	*1	2,311.00	481.00	386.00	58.00	481.00	663.00	75
8925-60	60	02"	04"	26"	20"	18"	29 1/2"	12 1/2"	24 1/2"	19"	8"	1	6,235.00	579.00	579.00	87.00	663.00	1,000.00	175
8925-100	100	02"	04"	34"	27"	22"	29 1/2"	24 1/2"	24 1/2"	19"	12"	2	8,858.00	915.00	767.00	124.00	835.00	1,261.00	280
8925-200	200	02"	04"	34"	27"	22"	41 1/2"	24 1/2"	36 1/2"	27"	12"	3	13,128.00	1,923.00	1,154.00	182.00	1,100.00	1,620.00	370

*Grate is 12 x 12"

REGULARLY FURNISHED: Fabricated Steel Body with Duco Coating and Sediment Pan w/Stainless Steel Bucket w/Perforated Back, Secondary Screen and Heavy Duty Cast Iron Grating.

