



TL250 T-Link Internet/Intranet Alarm Communicator

- Compatible with PowerSeries (v3.24 and higher) and MAXSYS (v3.31 and higher) control panels
- Works over local LAN/WAN network or the Internet
- 128-bit AES encryption (NIST approved)
- Supports DHCP (dynamic IP addresses)
- Low network bandwidth requirements
- Compatible with 10/100BaseT networks
- Reports events to 2 different receiver IP addresses
- Polling and hardware substitution protection
- Instant, always-on IP communication
- Software upgrades via network
- 4 on-board programmable inputs and 2 programmable voltage outputs as stand-alone module
- Programmable through the system keypad, PK5500 LCD keypad or T-Link Console software
- Download control panel via Internet with DLS software
- Compatible with Sur-Gard System I/II/III/IV monitoring station receivers
- UL standard & encrypted line security
- ULC passive or active line security levels A₁-A₄

Approval Listings: FCC/IC, UL/ULC, CSFM, NIST (AES Encryption Validation)



TL255 T-Link Internet/Intranet Alarm Communicator

- Compatible with IMPASSA control panel
- Panel remote uploading & downloading via internet/intranet using DLS IV
- Programmable using DLS IV or keypad
- Supervision heartbeat via internet/intranet
- 128 Bit AES Encryption
- Full event format
- SIA and Contact ID protocol

Approval Listings: FCC/IC, UL/ULC, CSFM, NIST (AES Encryption Validation)



TL260 T-Link Internet/Intranet Alarm Communicator

- Compatible with PC1864/PC1832/PC1616 control panels (v4.1 and higher)
- Panel remote uploading & downloading via internet/intranet using DLS IV
- Programmable using DLS IV or keypad
- Supervision heartbeat via internet/intranet
- 128 Bit AES Encryption
- Full event format
- SIA protocol
- Contact ID Protocol (with PowerSeries v4.5 and communicator firmware v1.1 or higher)

Approval Listings: FCC/IC, UL/ULC, CSFM, NIST (AES Encryption Validation)

Coming Soon

- RS-422 interface to C24-HUB
-