

CLEANOUTS

FIG. 4810 FLOOR ACCESS COVER W/ROUND FRAME AND SCORIATED COVER

FUNCTION: Used in concrete floors and/or surfaced areas. Scoriated covers are used where floors are subject to ordinary foot traffic and normal loadings. The secured cover should be used wherever vandalism can be a problem.








Fig. 4810

OPTI0	NS:	ADD
-U	Vandal Proof Screws	58.00
	Cover Drilled in Center and furnished with	
	1/4"-20 x 2 1/2" Long Screw	90.00
	Smooth Top for Flush-Type Cover	See Fig. 4725


		PLUG SIZE	02"	03"	04"	05"	06"	08"
		B - DIA:	4 1/2"	5 3/4"	6 1/2"	6 1/2"	8 1/2"	10 1/2"
	COVER MATERIAL	C - COVER DIA:	4 "	5 1/2"	6"	6"	8"	10"
4810	†Nickel Bronze (-NB)		213.00	213.00	213.00	213.00	371.00	538.00
	Polished Bronze (-PB)		192.00	192.00	192.00	192.00	343.00	473.00
		APPROX WT. LBS.	2	3	5	5	9	13

REGULARLY FURNISHED: Secured Scoriated Nickel Bronze Cover and Frame with Anchor Lugs.

FIG. 4890 ROUND DECK PLUG W/THREADED SPANNER WRENCH COVER

FUNCTION: Used as floor cleanout for drainage lines. The threaded machine fit cover is watertight and requires a spanner wrench for removal.





OPTION	IS:	ADD
-SH	Securing Holes (Fig. DX4890)	74.00
-SW	Spanner Wrench	

		A - PLUG SIZE	02"	03"	04"	05"	06"	08"
		B - DIA:	4"	4 3/4"	6"	8"	8 3/4"	10 3/4"
	COVER MATERIAL	C	2"	3"	3"	3 1/2"	3 1/2"	3 1/2"
4890	†Nickel Bronze (-NB)		296.00	415.00	459.00	727.00	792.00	1,542.00
	Polished Bronze (-PB)		273.00	368.00	413.00	668.00	734.00	1,237.00
		APPROX WT. LBS.	3	7	9	10	12	18
DX4890	†Nickel Bronze (-NB)		925.00	1,043.00	1,088.00	-	-	-
	Polished Bronze (-PB)		902.00	996.00	1,042.00	-	-	-
		APPROX WT. LBS.	8	13	17	-	-	-

REGULARLY FURNISHED: All Nickel Bronze with Polished Scoriated Cover.

