



## WS4926 Wireless Photoelectric Smoke Detector

- Automatic drift compensation
- Built-in 85dB horn
- Local test button
- Low profile design
- High/Low sensitivity reporting
- Easy-maintenance removable smoke chamber
- Non-contact sensitivity reading with handheld test meter (FSD-100)
- Long-life lithium batteries included
- UL/ULC listed for residential applications
- Low battery indication

Approval Listings: FCC/IC, UL/ULC, CSFM



## WT4901 2-Way Wireless Indoor Siren

- Siren Output – 85dB
- Siren sounds for alarms, door chimes, entry/exit delay and troubles
- Transmits RF status, low battery and tamper condition
- Front and back tamper detection
- Nominal battery life - 1 year
- Compatible with ALEXOR & IMPASSA
- Onboard test button

Approval Listings: FCC/IC, UL/ULC, SIA CP-01, CSFM



## WT4911 2-Way Wireless Outdoor Siren

- Siren Output – 100dB
- Siren sounds for alarms and squawks
- Strobe light functionality for visual indication
- Provides temperature to WT5500 wire-free keypad
- Transmits RF status, low battery and tamper condition
- Large print area for company logo
- Front and back tamper detection
- IP34 rating
- Nominal battery life – 2-3 years
- Compatible with ALEXOR & IMPASSA
- Remote test capability

Approval Listings: FCC/IC, UL/ULC, SIA CP-01



## WS4985 Wireless Flood Detector

The wireless flood detector is based on the WS4945 wireless door/window contact that is connected to a water probe through a 6 foot-wire. The product is enrolled as a flood zone detector with the following DSC control panels: ALEXOR, PowerSeries 9047, IMPASSA, PC1616, PC1832, PC1864, PC4020, and is fully supervised.

- Built-in reed switch
- Normally closed external contact input
- 1 lithium battery included
- Case and wall tamper
- End-of-line resistor
- 4 year battery life

Approval Listings: FCC/IC