

SKS-HT870 BLACK

7.1-Channel Home Theater Speaker System



SKF-770 Dual-Drive 2-Way Front Speakers

- 3 1/4" (8 cm) Cone Woofer x 2 • 1" (2.5 cm) Balanced-Dome Tweeter • Gloss-Finished Top Panel
- Max. Input Power: 130 W • WHD: 10 3/16" x 4 1/2" x 10 3/16" (262 x 1050 x 262 mm) • 11.5 lbs. (5.2 kg)

SKC-770 Dual-Drive 2-Way Center Speaker

- 3 1/4" (8 cm) Cone Woofer x 2 • 1" (2.5 cm) Balanced-Dome Tweeter • Gloss-Finished Side Panels
- Max. Input Power: 130 W • WHD: 16 1/16" x 4 1/2" x 4 3/4" (430 x 115 x 121 mm) • 4.9 lbs. (2.2 kg)

SKR-770/SKB-770 Full-Range Surround/Surround Back Speakers

- 3 1/4" (8 cm) Cone • Max. Input Power: 130 W • WHD: 4 1/2" x 9 1/16" x 3 3/4" (115 x 230 x 96 mm) • 2.2 lbs. (1.0 kg) *Note: All speakers feature an impedance of 6 ohms and color-coded speaker terminals and cable. All except the front speakers are wall-mountable.*

SKW-770 Bass Reflex Powered Subwoofer

- 10" (25 cm) Cone • Down-Firing • Output-Level Control • Gloss-Finished Front Panel
- Max. Output Power: 290 W • WHD: 10 13/16" x 19 15/16" x 16 3/16" (275 x 507 x 411 mm) • 25.6 lbs. (11.6 kg)

SKS-HT750 BLACK

7.1-Channel Home Theater Speaker System



SKF-750F 2-Way Acoustic-Suspension Front Speakers

- 3 1/4" (8 cm) Cone Woofer x 2 • 1" (2.5 cm) Balanced-Dome Tweeter • Magnetically Shielded
- Max. Input Power: 110 W • WHD: 5 1/2" x 14" x 3 11/16" (140 x 355 x 93 mm) • 4.0 lbs. (1.8 kg)

SKC-750C 2-Way Acoustic-Suspension Center Speaker

- 3 1/4" (8 cm) Cone Woofer x 2 • 1" (2.5 cm) Balanced-Dome Tweeter • Magnetically Shielded
- Max. Input Power: 110 W • WHD: 14" x 5 1/2" x 3 11/16" (355 x 140 x 93 mm) • 4.0 lbs. (1.8 kg)

SKM-750S/SKB-750 2-Way Acoustic-Suspension Surround/Surround Back Speakers

- 3 1/4" (8 cm) Cone Woofer • 1" (2.5 cm) Balanced-Dome Tweeter • Magnetically Shielded
- Max. Input Power: 110 W • WHD: 5 1/2" x 14" x 3 11/16" (140 x 355 x 93 mm) • 2.9 lbs. (1.3 kg)

**All speakers feature an impedance of 8 ohms, color-coded, push-type speaker terminals, speaker cables and rubber spacers. The center speaker has a base for horizontal mounting.*

SKW-750 Bass Reflex Powered Subwoofer

- Built-In 230 W Amplifier • Down-Firing • Auto-Standby/On Circuitry • Output Level Control
- 10" (25 cm) Cone • WHD: 10 13/16" x 19 15/16" x 16 3/16" (275 x 507 x 411 mm) • 24.7 lbs. (11.2 kg)

SKS-HT690 BLACK

5.1-Channel Home Theater Speaker System



SKF-690 2-Way Acoustic-Suspension Front Speakers

- 3 1/4" (8 cm) Cone Woofer • 1" (2.5 cm) Balanced-Dome Tweeter
- Max. Input Power: 130 W • Gloss Finished • Magnetically Shielded
- WHD: 4" x 6 11/16" x 4 1/8" (102 x 170 x 105 mm) • 2.2 lbs. (1.0 kg)

SKC-690 2-Way Acoustic-Suspension Center Speaker

- 3 1/4" (8 cm) Cone Woofer x 2 • 1" (2.5 cm) Balanced-Dome Tweeter
- Max. Input Power: 130 W • Gloss Finished • Magnetically Shielded
- WHD: 10 7/8" x 4 3/16" x 4 3/16" (277 x 110 x 110 mm) • 3.7 lbs. (1.7 kg)

SKR-690 Full-Range Acoustic-Suspension Surround Speakers

- 3 1/4" (8 cm) Cone • Max. Input Power: 130 W • Gloss Finished
- Magnetically Shielded • WHD: 4" x 6 11/16" x 4 1/8" (102 x 170 x 105 mm) • 2.0 lbs. (0.9 kg)

Note: All speakers feature an impedance of 6 ohms, color-coded speaker terminals and cable, and wall-mounting capability.

SKW-780 Bass Reflex Powered Subwoofer

- 10" (25 cm) Cone • Rated Output Power: 120 W (Minimum Continuous Power: 4 Ohms, 100 Hz, 1%, FTC) • Down-Firing • Gloss Finished • Output Level Control
- WHD: 10 13/16" x 19 15/16" x 16 3/16" (275 x 507 x 411 mm) • 25.6 lbs. (11.6 kg)

SKS-HT540 BLACK

7.1-Channel Home Theater Speaker System



SKF-540F 2-Way Bass Reflex Front Speakers

- 5" (12 cm) OMF Diaphragm Woofer x 2 • 1" (2.5 cm) Balanced-Dome, Floating Tweeter • Magnetically Shielded • Impedance: 8 Ohms
- Max. Input Power: 130 W • WHD: 6 3/16" x 17 1/16" x 7 7/8" (157 x 433 x 200 mm) • 8.4 lbs. (3.8 kg)

SKC-540C 2-Way Bass Reflex Center Speaker

- 5" (12 cm) OMF Diaphragm Woofer x 2 • 1" (2.5 cm) Balanced-Dome, Floating Tweeter • Magnetically Shielded • Impedance: 8 Ohms
- Max. Input Power: 130 W • WHD: 17 1/16" x 6 3/16" x 7 7/8" (433 x 157 x 200 mm) • 8.4 lbs. (3.8 kg)

SKM-540S/SKB-540 2-Way Bass Reflex Surround/Surround Back Speakers

- 3 1/8" (8 cm) Cone Woofer • 3/4" (2 cm) Ceramic Tweeter • Impedance: 8 Ohms
- Max. Input Power: 130 W • WHD: 6 7/8" x 10 7/16" x 4" (175 x 265 x 102 mm) • 3.1 lbs. (1.4 kg)

SKW-540 Bass Reflex Powered Subwoofer

- Built-In 230 W Amplifier • Auto-Standby/On Circuitry • Output Level Control
- 10" (25 cm) Cone • WHD: 10 13/16" x 18 3/8" x 16 7/8" (275 x 473 x 449 mm) • 25.4 lbs. (11.5 kg)



SKW-204 BLACK

Bass Reflex Powered Subwoofer

- Built-In 230 W Amplifier • 10" (25 cm) Cone
- Auto-Standby/On Circuitry • Continuously Variable Crossover (50 Hz–200 Hz) • Phase Switch (0° or 180°) • Line Level Inputs • Impedance: 100 k-ohms • Frequency Response: 25 Hz–150 Hz
- WHD: 10 13/16" x 18 3/8" x 16 7/8" (275 x 473 x 428 mm) • 26.0 lbs. (11.8 kg)

HTX-22HDX BLACK

Ultra-Compact HD Home Theater System

A Simple Way to Add Audio Power



HTX-22HDXPAW 5.1-Channel Amplifier with Built-in Subwoofer

- 25 W/Ch (FL/FR/C/SL/SR) at 6 Ohms, 1 kHz, 1%, 1 Channel Driven, FTC; 60 W (Subwoofer) at 3 Ohms, 100 Hz, 1 Channel Driven, FTC • HDMI® Support for 3D, Audio Return Channel, DeepColor™, x.v.Color™, LipSync, Dolby® TrueHD, DTS-HD Master Audio™, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC • 3 HDMI Inputs and 1 Output • Dolby® TrueHD and DTS-HD Master Audio™ Decoding • VLSC™ (Vector Linear Shaping Circuitry) for Front L/R Channel • Burr-Brown 192 kHz/24-Bit DACs (PCM1690) for all Channels • Jitter-Cleaning Circuit Technology • Overlaid On-Screen Display (OSD) via HDMI • EX.Bass for Deeper, More Dynamic Bass • 4 DSP Modes for Gaming®: Rock, Sports, Action, and RPG • Theater-Dimensional Virtual Surround Function • Music Optimizer™ for Compressed

- Digital Music Files • RiHD (Remote Interactive Over HDMI) for System Control • Compatible with RI (Remote Interactive) Dock for iPod® • 6 1/2" (16 cm) Cone • WHD: 8 3/16" x 13 1/4" x 12 3/16" (217 x 337 x 310 mm) • 20.9 lbs. (9.5 kg)

** Available only in 5.1-channel speaker configuration*

HTX-22HDXST Full-Range Bass Reflex Speakers

- 3 1/4" (8 cm) Cone • Max. Input Power: 40 W • Impedance: 6 Ohms • Frequency Response: 70 Hz–20 kHz • Magnetically Shielded • Gloss Finished • WHD: 4" x 6 5/16" x 4 3/8" (101 x 161 x 111 mm) • 1.8 lbs. (0.8 kg)



Theater-Dimensional RiHD RI