


FLOOR DRAINS

FIG. 2633 LIGHT DUTY HOPPER DRAIN WITH FLAT BOTTOM STRAINER

FUNCTION: Hopper type drain for use in areas not subject to traffic.







OUTLET VARIATIONS (Specify type of outlet and pipe size in inches.)

	Outlet Designation	
	Type Outlet Type/Pipe Size aulk	
	Y02, Y03, Y04d	
OPTIO -DBS	NS: Alum Dome Bottom Strainer	ADD 71.00
-F -FC	Flange, Cast IronFlange w/Flashing Clamp	
-G -P	Galvanized CI Trap Primer Connection	


A OUTLET SIZE	TOP SIZE	FREE Area SQ in	†DUCO CI			APPROX. WEIGHT LBS
02, 03, 04"	12" SQ	28	487.00	906.00	952.00	30


REGULARLY FURNISHED: Duco Cast Iron Body with Flat Bottom Strainer.

FIG. 2640 BLOOD AND WATER DRAINS

FUNCTION: Used in packing house slaughtering areas. Consists of two individual drains. Slotted grate drain permits drainage of animal blood to separate storage tank while adjacent drain connected to sewer is covered by solid ground joint plug. When area is to be washed down, the solid plug is put on the blood drain and the slotted grate on the sewer water drain, thus water used in the cleaning operation will be directed to sewer and will not enter the blood storage tank.







OUTLET VARIATIONS (Specify type of outlet and pipe size in inches.)

				,
Outlet Ty	ype	Outlet Designation Outlet Type/Pipe SizeC02, C03, C04	Body HT. DIM.	ADD
		L02, L03, L04		
		LXH02, LXH03, LXH04		
Threaded		T02, T03, T04	2	95.00
		Y02, Y03, Y04		
OPTION		Charican Ol as		ADD
-FBSCI		Strainer, CI, ea		
-G		<u> </u>		
-M		Tops		
-RB	RB Grate &	Plug	1	,360.00

	A OUTLET SIZE	TOP	AREA	†DUCO CI GRATE & PLUG	DUCO CI w/BRZ GRATE & PLUG (RB)	w/NB GRATE	
0	02, 03, 04"	9"	10.3	915.00	2,275.00	2,598.00	50

REGULARLY FURNISHED: Two (2) Duco Cast Iron Bodies with Flashing Collar and Bronze Rim, Cast Iron Grate and Ground Joint Plug.

†REGULARLY FURNISHED



234