



VDM-1

DIGITAL INTERCONNECT: 75Ω COAX



THE DEFINITION OF VDM: AudioQuest/CinemaQuest VDM Series cables are designed to minimize distortion across an extremely wide bandwidth. A 75Ω cable is like a conduit which has to carry relatively low frequency analog video (Composite, up to 4.2MHz), or super sensitive digital audio (SP/DIF, up to 24.576 MHz), or uncompressed High Definition video (HDTV, up to 750 MHz), or cable TV/broadband (CATV, up to 1 GHz). AQ/CQ VDM (preterminated cables) and VSD (bulk installation cables) cables are designed to carry all these signals with minimum interference from the cable.

THE INGREDIENTS: VDM-1 uses a 2.5% Silver Center Conductor (2.5% SPC) insulated with Hard Cell Foam (HCF). Normal 1.25% silver-plate greatly improves high frequency performance for a fraction of the cost of solid silver. A 2.5% silver conductor is much closer to all silver, still for a fraction of the cost. Nitrogen Injected HCF reduces distortion caused by the insulating material. The combination foil and Silver-Plated braid shield provides 100% protection coverage and lower distortion. Gold-Plated RCA plugs are professionally attached with superior AudioQuest solder. BNC, Antenna and F connectors are also available.