



GS2065 GPRS Cellular Alarm Communicator

- Compatible with ALEXOR Wireless Panel
- Back up and primary GPRS alarm communication
- Panel remote uploading/downloading support via GPRS
- Supervision heartbeats via GPRS
- 128-bit AES encryption via GPRS
- SIA protocol
- SIM Card (included)
- PC-Link connection
- Signal strength and trouble display
- Remote activating and programming through C24 Communications
- Full event reporting
- Quad-Band: 850 MHz, 1900 MHz, 900 MHz and 1800 MHz
- Compatible with Sur-Gard System I/II/III/IV monitoring station receivers
- UL standard & encrypted line security
- Antenna Extension Kits available: ANT-15Q, ANT-25Q, ANT-50Q
- Contact ID protocol (with ALEXOR firmware v1.1 and communicator firmware v1.1 or higher)
- Command and Control via SMS

Approval Listings: FCC/IC, PTCRB, UL/ULC, NIST (AES Encryption Validation), CSFM, AT&T/Rogers



TL265GS Internet and GPRS Dual-Path Alarm Communicator

- Compatible with ALEXOR Wireless Panel
- Fully redundant Internet and GPRS dual-path alarm communication
- Integrated call routing
- Panel remote uploading/downloading support via GPRS and Internet
- Supervision heartbeats via GPRS and Internet
- 128-bit AES encryption via GPRS and Internet
- Full event reporting
- SIA protocol
- SIM Card (included)
- PC-Link connection
- Signal strength and trouble display
- Remote activating and programming through C24 Communications
- Quad-Band: 850 MHz, 1900 MHz, 900 MHz and 1800 MHz
- Compatible with Sur-Gard System I/II/III/IV monitoring station receivers
- UL standard & encrypted line security
- Active GS account is required to use IP function
- Antenna Extension Kits available: ANT-15Q, ANT-25Q, ANT-50Q
- Contact ID protocol (with ALEXOR firmware v1.1 and communicator firmware v1.1 or higher)
- Command and Control via SMS

Approval Listings: FCC/IC, PTCRB, UL/ULC, NIST (AES Encryption Validation), CSFM, AT&T/Rogers



3G2055 HSPA Cellular Alarm Communicator

- Compatible with IMPASSA Wireless Panel
- Back up and primary HSPA alarm communication
- Panel remote uploading/downloading support via HSPA
- Supervision heartbeats via HSPA
- 128-bit AES encryption via HSPA
- SIA and Contact ID protocol
- SIM Card (included)
- Remote activating and programming through C24 Communications
- Signal strength and trouble display via IMPASSA
- Full event reporting
- Dual-Band HSPA: 850 MHz, 1900 MHz
- Quad-Band GPRS/EDGE: 850 MHz, 1900 MHz, 900 MHz and 1800 MHz
- Compatible with Sur-Gard System I/II/III/IV monitoring station receivers
- UL standard & encrypted line security
- Command and Control via SMS
- 2-Way voice over cellular

Approval Listings: FCC/IC, PTCRB, UL/ULC, CSFM, AT&T/Rogers

Coming Soon

- Direct connection to C24 Interactive via cellular