

**FSB-210 Series Addressable Photoelectric Smoke Detectors**  
**FSB-210B (without Heat Sensor)**  
**FSB-210BT (with Heat Sensor) – Fixed Heat With Rate Of Rise**  
 (rate of rise feature not UL listed)

*Note: Not available in Canada*

- Automatic drift compensation
- Easy-maintenance removable smoke chamber
- Non-contact sensitivity reading with handheld test meter (FSD-100)
- Self diagnostics

Approval Listings: FCC/IC, UL, CSFM



**AML-770B Loop Isolator Module**

- Can be used to isolate burglary detectors from fire detectors on the same wire run

Approval Listings: FCC/IC, UL/UJLC



**AMX-400 Loop Repeater/Isolator Module**

- Can be used to repeat and re-power the AML loop to allow for longer wire runs
- Requires 12 VDC power source
- Will isolate the wire run in the event of a problem
- Provides additional 170 mA

Approval Listings: FCC/IC, UL/UJLC



**Addressable Contact Modules**

Model	Description
AMP-700	Door/Window contact with built-in reed switch
AMP-701	Door/Window contact with normally closed external contact input
AMP-702	Fire point module with normally open, EOL resistor supervised external contact input
AMP-704	4-zone door/window contact with normally closed, single or double EOL inputs

Approval Listings: FCC/IC, UL/UJLC

