

ROOF DRAINS


FIG. 1670 FLAT STRAINER - SIDE OUTLET GUTTER DRAIN

FUNCTION: Used in gutters where a drain is required for connecting to the downspout leader. Flashing arrangement design permits removal of dome or flat strainer without disturbing flashing clamp and gutter liner. Does not obstruct traffic.









OUTLET VARIATIONS (Specify type of outlet and pipe size in inches.)

	Outlet	
	Designation	
Outlet Type	Outlet Type/Pipe Size	ADD
Threaded	T02. T03. T04	N/C

OPTI0	NS:	ADD
-CP	Chrome Plated Grate	138.00
-G	Galvanized Cast Iron	100.00
-NB	Nickel Bronze Grate	124.00
-PB	Polished Bronze Grate	74.00
-U	Vandal Proof Grate	33.00
-SSM	SS Mesh on Grate	71.00
	2" High Water Dam on Collar	227.00

A OUTLET SIZE	В	С	D	FLANGE DIA	FREE AREA SQ IN	†DUCO CI RB TOP	ALL ROUGH BRZ (-BB)	APPROX. WEIGHT LBS
02"	2 1/2"	2 1/2"	4"	6"	7	322.00	528.00	7
03"	3"	3"	5"	6"	7	438.00	791.00	10
04"	3 1/2"	4"	6 1/4"	6"	7	438.00	791.00	12


REGULARLY FURNISHED: Duco Cast Iron Body with Bronze

Flashing Clamp and Bronze Top Secured with Brass Screws.

FIG. 1680 LOW DOME - SIDE OUTLET GUTTER DRAIN

FUNCTION: Used in gutters where a drain is required for connecting to the downspout leader. Flashing arrangement design permits removal of dome or flat strainer without disturbing flashing clamp and gutter liner. Intercepts debris and allows adequate drainage in gutters and valleys.





OUTLET VARIATIONS (Specify type of outlet and pipe size in inches.)

Outlet Designation Outlet Type/Pipe Size	ADD N/C
	Designation

OPTI0	NS:	ADD
-CP	Chrome Plated Dome	
	Galvanized Cast Iron	100.00
-NB	Nickel Bronze Grate	124.00
-PB	Polished Bronze Grate	74.00
-SSM	SS Mesh on Dome	143.00
-U	Vandal Proof Grate	33.00
	2" High Water Dam on Collar	227.00

A OUTLET SIZE	В	C	D	FLANGE DIA	FREE AREA SQ IN	†DUCO CI RB TOP	ALL ROUGH BRZ (-BB)	APPROX. WEIGHT LBS
02"	2 1/2"	2 1/2"	4"	6"	8	322.00	528.00	7
03"	3"	3"	5"	6"	8	438.00	791.00	10
04"	3 1/2"	4"	6 1/4"	6"	8	438.00	791.00	12

REGULARLY FURNISHED:

Duco Cast Iron Body with Bronze Flashing Clamp and Bronze Top Secured with Brass Screws.