



Control4® Wireless Fireplace Switch

Control4® Wireless Fireplace Switch C4-FS1-Z

The Control4® Wireless Fireplace Switch makes it easy to integrate control of standard gas fireplaces into any Control4 system. Enjoy fireplace control from any room in your home, and integrate your fireplace into a 'wakeup' or 'goodnight' scene. The Control4 Wireless Fireplace Switch is perfect for extending control to any standard gas fireplace.

- Energy Management—Make your fireplace an automatic part of your HVAC system to provide additional heating beyond your HVAC system capabilities.
- Personalized Control—Enjoy romantic evenings when your fireplace is integrated with a predetermined lighting scene.
- Remote Management—Control the fireplace from any Control4 user interface whether you're in the next room or the next state with 4Sight or a MyHome license.
- Flexible—Supports most standard gas fireplaces.

Control4® Wireless Fireplace Switch

Model Number	C4-FS1-Z
Power Requirements	
Power requirements	120 VAC +/- 10%, 60/50 Hz 36 VAC low-voltage power supply
Supported load types (via dry contact output)	Millivolt low-voltage control 24 VAC (up to 240W) 30 V DC (up to 10A)
Power consumption	300mW when off 400mW when on
Multi-gang derating	N/A
Environmental Requirements	
Operating temperature	32° F to 104° F (0° C to 40° C)
Humidity	5% to 95% (non-condensing)
Storage	-4° F to 158° F (-20° C to 70° C)
Communications	
Control communications	ZigBee (IEEE 802.15.4), 2.4 GHz, 15-channel, spread-spectrum radio, mesh networking
Dimensions	
H x W x D	4.6" x 2.75" x 1.6" (117 mm x 70 mm x 41 mm)
Weight	4.9 oz (139 g)
Optional Accessories	
Button Color Change Kits	C4-CKSWI
Available colors	AL, BL, BR, IV, LA, WH

Color key: AL=Almond, BL=Black, BR=Brown, IV=Ivory, LA=Light almond, WH=White

For product photos, documentation and installation instructions, visit:
<http://www.control4.com/dealer/products/climate/fireplace-switch/>

