VENDED

Single Pocket Tumble Dryers 50 lb Tumble Dryer

75 lb Tumble Dryer

Speed Queen®

BUILT FOR RELIABLE PERFORMANCE.

For more than a century, Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.

EFFICIENCY = PROFITABILITY

The faster and more efficient your tumble dryers are, the more profitable your store will be. Our 50 and 75 lb tumble dryers feature large cylinders and a design that emphasizes speed and efficiency. These tumble dryers are perfect for drying oversized items such as quilts and your customers' largest loads.




DURABLE, WORRY-FREE OPERATION

Extra-large stainless steel doors and heavy-duty hinges ensure these machines will stand up to the repeated use of high-traffic vended laundries. Speed Queen tumble dryers feature an all-belt drive system, which means they're less noisy and cheaper to maintain. Our fine mesh lint screen is self-cleaning, depositing lint into a large storage area for easy, once-per-day removal. Our patented cylinder design allows drywall screws to pass through oval perforations, preventing damage to the metal surrounding the cylinder.

EXPERT FINANCING SOLUTIONS

Experience. Knowledge. Guidance. Speed Queen Financial Services has the tools to define a viable financial strategy, whether you're a first time investor or sophisticated entrepreneur. See for yourself how our progressive programs, successful track record and unbeatable laundry expertise can help you succeed. Visit SpeedQueen.com/finance to learn more.





DEDICATED TO A HIGHER STANDARD.

ACTIVATIONS

SINGLE DROP

This classic, easy-to-use all-metal design reduces coin jamming and easily accommodates reprogrammed changes in vend prices.

DUAL DROP

The dual drop offers both single dollar and \$.25 options, ideal for larger capacity machines.

AFTER-MARKET CARD READERS

We'll prep your machine for later installation of a card payment system, which increases customer loyalty due to its convenience and helps you avoid transporting large amounts of coins.



CONTROLS

QUANTUM™ GOLD

In addition to its network capabilities and off-site management features, Quantum[™] Gold offers additional owner and customer benefits such as PC/PDA programming and machine audit capabilities, as well as time-of-day pricing of up to a year in advance, a free "lucky cycle" for loyal customers and the ability to interface with the store owner's card manufacturer of choice. As gas prices continue to rise, Quantum Gold enables you to set dry cycle times right down to the second for maximum profitability.

MICRO-DISPLAY

Our Micro-Display Control (MDC) clearly displays the vend price and keeps customers informed throughout the drying process with cycle status lights and a digital cycle countdown. Interfacing with a variety of aftermarket card reader systems, MDC offers four cycle selections, basic audit features and comes installed with a single coin drop.



SINGLE POCKET TUMBLE DRYER SPECIFICATIONS

	ST050	ST075
Control	Quantum Gold, MDC	Quantum Gold, MDC
Dry Capacity- Ib (kg)	50 (22.7)	75 (34.0)
Filling Ratio - Ib (kg)	20:1 = 58 (26.4)	20:1 = 70 (31.7)
Width - in (mm)	38 5/8" (981)	38 5/8" (981)
Depth - in (mm)	48.25" (1226)	54.25" (1378)
Height - in (mm)	76 5/8" (1946)	76 5/8" (1946)
Cylinder Depth - in (mm)	30" (762)	36" (914)
Cylinder Diameter - in (mm)	37" (939)	37" (939)
Cylinder Volume - cu. ft. (liters)	18.6 (528)	22.4 (634)
Door Opening Size - in (mm)	26 7/8" (683)	26 7/8" (683)
Airflow - cfm (liter/sec)	60Hz: 750 (354) 50Hz: 750 (354)	60Hz: 920 (434) 50Hz: 750 (354)
Air Outlet Diameter - in (mm)	8″ (203)	8″ (203)
Energy Data Gas Steam Electric	60Hz - 130,000 Btu/hr (38.1 kW) 50Hz - 130,000 Btu/hr (38.1 kW) At 100 psi (6.9 bar): 5.1 BHP 178,000 Btu/hr (52.0 kW) 30 kW	60Hz - 165,000 Btu/hr (48.3 kW) 50Hz - 165,000 Btu/hr (48.3 kW) At 100 psi (6.9 bar): 6.1 BHP, 210,300 Btu/hr (61.6 kW) 30 kW
Electrical Specifications Gas and Steam 120/60/1; 2W+6 200-208/240/60/1; 2W+6 200-208/240/60/1; 2W+6 200-208/240/60/3; 3W+6 380/60/3; 3W+6 380/60/3; 3W+6 380/60/3; 3W+6 (Steam Only) 440/60/3; 3W+6 230-240/50/1; 2W+6 200-208/20/3; 3W+6 230-240/50/3; 3W+6 200/50/3; 3W+6 230-240/50/3; 3W+6 200/50/3; 3W+6 240/60/3; 3W+6 200-208/60/3; 3W+6 380/60/3; 3W+6 240/60/3; 3W+6 380/60/3; 3W+6 240/60/3; 3W+6 240/50/1; 2W+6 200/50/3; 3W+6 200/50/3; 3W+6 200/50/3; 3W+6 200/50/3; 3W+6 200/50/3; 3W+6 200/50/3; 3W+6 200/50/3; 3W+6 240/50/3; 3W+6 200/50/3; 3W+6 380/50/3; 3W+6 200/50/3; 3W+6 380/50/3; 3W+6 200/50/3; 3W+6 380/50/3; 3W+6	Amps 9.3 5.1/5.1 2.8/2.8 (4.0/4.0) 1.6 (2.0) 1.4 (1.9) 1.4 (1.9) 6.3 (6.9) 3.3 (4.2) 3.1 (4.3) 1.6/1.6 (2.0/2.0) 89 (88) 79 (78) 47 (48) 41 (41) 38 (38) 93 (95) 84 (85) 73 (75) 79 (78) 47 (48) 43 (44)	Amps 13.8 7.6/7.6 3.8/3.8 (4.3/4.3) 1.8 (2.1) 1.9 (2.1) 1.9 (2.1) 1.9 (2.1) 1.9 (2.1) 6.7 (7.0) 3.5 (4.5) 3.5 (4.9) 1.8/1.8 (2.1/2.1) 89 (88) 79 (78) 47 (48) 41 (41) 38 (38) - 84 (85) 73 (75) 79 (78) 47 (48) 43 (44)
Motor Size - HP (W) Fan Cylinder	1/2 (375) 1/2 (375)	3/4 (559) 3/4 (559)
Plumbing Connections Gas Steam	1/2" - NPT 3/4" - NPT	1/2" - NPT 3/4" - NPT
Shipping Dimensions - Width Approx in (mm) Depth Height	41 1/2" (1054) 52 1/8" (1323) 81" (2057)	41 1/2" (1054) 56 13/32" (1433) 81" (2057)
Net Weight - Ib (kg)	545 (247)	615 (279)
Shipping Weight - Ib (kg)	602 (273)	677 (307)
Agency Approvals Gas Australia Gas Electrical & Steam	CSA Star, CSA Flame, _C CSA _{US} , CE, Australia Gas _C CSA _{US} , CE	CSA Star, CSA Flame, cCSA _{US} , CE, cCSA _{US} , CE

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000. Printed in the U.S.A.

speedqueen.com

Speed Queen®