



VNS2252 - Internal Rechargeable Battery (Built-In)



The optional VNS2252 Internal Rechargeable Battery is designed to provide indoor/outdoor built-in power backup to VNS2200 wireless audio/visual controllers and VNS1021 wireless controllers.

The VNS2252 is installed inside the VNS2200 or VNS1021 and used as a main power source, providing approximately 24 hours of stand-by time and 1-2 hours of operation time.

Key Features:

- Absorbent Glass Mat Technology for Superior Performance
- Rugged Impact Resistant ABS Case and Cover (UL94-HB)
- Approved for Transport by Air, D.O.T., I.A.T.A., F.A.A. and C.A.B. Certified
- Valve Regulated, Spill Proof Construction Allows Safe Operation
- UL Recognized Under MH 20845

Options, Accessories and Complementary Products:

Part Number	Description
VNS1021	Wireless Controller
VNS2200	Wireless Audio/Visual Controller

Specifications:

Dimensions	3.78" x 2.28" x 1.69" (W x H x D)	Internal Resistance	100 Milliohms
Weight	1.2 lbs.	Operating Temperature	Charge: -4° - 122°F Discharge: -40° - 140°F
Nominal Voltage	12V	Material	Rugged Impact Resistant ABS Case & Cover
Energy Density	1.29 W-h/in ³	Termination	Quick Disconnect Tabs
Specific Energy	14 W-h/lb	Limited Warranty	One Year Parts and Labor
Maximum Discharge	4.2 Amps		

*Specifications Are Subject to Change Without Notification