

## **FLEXIFUSER**<sup>™</sup>

- High density wood fiber composite construction provides rigid structure of the outer cabinet
- Black Melamine finish provides a tough durable coat that is easy to clean and looks great!
- High density fiberglass panel absorbs high frequencies and helps eliminate flutter echo.
- 6 slats can be fixed into place during assembly, or remain adjustable to change the sound of the room

The Primacoustic FlexiFuser is a 24" x 48" x 8" variable pitch diffuser and absorber that employs a series of adjustable slats, allowing the engineer a way to customize the reflective pattern. Behind the slats, a full-size, 2" thick high-density fiberglass panel absorbs excessive energy from 250Hz and up. This combination of adjustable slats and absorptive panel helps to eliminate standing waves and flutter echo, and is tunable to any room or listening position. The FlexiFuser enclosure is made from MDF wood composite with an easy to clean black melamine finish and ships flat to save freight. Final assembly is performed on site using a household screwdriver, and building a FlexiFuser takes about 15 minutes from start to finish.

## SPECIFICATIONS:


| - | 0. 20. 10. 10. 10. |  |  |  |  |  |
|---|--------------------|--|--|--|--|--|
| I | Frame Material     | Black melamine laminated MDF outer & slats                                     |  |  |  |  |
|   | Dimensions         | 24" (610mm) x 48" (1219mm) x 8" (203mm)  |  |  |  |  |
|   | Panel Material     | Formed, semi-rigid inorganic glass fibers;<br>Density 6.0 lbs. pcf. (96 kg/m3) |  |  |  |  |
|   | Fabric Facing      | Acoustically transparent polyester, Grey only                                  |  |  |  |  |
|   | Order Number       | Z840 1135 08   |  |  |  |  |

## ABSORPTION CHARACTERISTICS:\*


Sound absorption coefficient data


| PANEL DEPTH | 125Hz | 250Hz | 500Hz | 1kHz | 2kHz | 4kHz | NRC  |
|-------------|-------|-------|-------|------|------|------|------|
| 2" Depth    | 0.45  | 0.83  | 1.07  | 1.00 | 1.01 | 1.00 | 1.00 |

<sup>\*</sup> Testing performed by Riverbank Acoustical Laboratories. The test method conformed explicitly with the requirements of the ASTM Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method: ASTM C 423-02a and E795-05.









Top panel removed to show slats.

## APPLICATION:

Diffusers mounted behind the listening position break up front to back room reflections and creat a sence of "air".

