



## WPT-EN1210 - Universal Wireless 900 MHz Transmitter



WPRP-EN5040

### Key Features:

- One Pre-Programmed ID
- 300' - 1,000' Range (Increased Using Data Repeater)
- Long-life Single Lithium Battery
- Low Battery Alert
- Built-In Dry Contact Closure
- Wall, Door or Surface Mount

The **WPT-EN1210 Universal Wireless 900MHz Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4800** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

The WPT-EN1210 provides a dry contact closure terminal for two-wire connection and can be set to normally open or normally closed.

When the WPT-EN1210 dry contact is activated, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

In addition, when the WPT-EN1210 is reset to its normal position, a cancellation alert can be sent.

The WPT-EN1210 can generate an automated message to report low battery status. The WPT-EN1210 also offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

The WPT-EN1210 includes mounting hardware.

**\*Note:** Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

### Options, Accessories and Complementary Products:

Part Number	Description
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)

### Specifications:

Dimensions	1.75" x 3.5" x 0.9" (W x H x D)	Activation Type	Dry Contact Switch
Weight	3 oz.	Programming	PC Based Programming Kit
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	Ivory	Frequency Range	900 MHz
Operating Temperature	-4° - 140°F	Paging Addresses	1
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor

\*Specifications Are Subject to Change Without Notification