



WPT-I210 - Universal Wireless 900 MHz Transmitter



Key Features:

- One Programmable ID
- 300' - 1,000' Range (Increased Using Data Repeater)
- Long-life Single Lithium Battery
- Low Battery Alert
- Built-In Dry Contact Closure
- Wall, Door or Surface Mount

The WPT-I210 Universal Wireless 900MHz Transmitter is designed to be used with a main wireless paging controller, such as the VS4800 or VNS5100. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

The WPT-I210 provides a dry contact closure terminal for two-wire connection and can be set to normally open or normally closed.

When the WPT-I210 dry contact is activated, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

In addition, when the WPT-I210 is reset to its normal position, a cancellation alert can be sent.

The WPT-I210 can generate an automated message to report low battery status. The WPT-I210 also offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

The WPT-I210 includes mounting hardware.

Options, Accessories and Complementary Products:

Part Number	Description
WPRP-I575	Wireless 900 MHz Repeater

Specifications:

Dimensions	1.75" x 3.5" x 0.9" (W x H x D)	Activation Type	Dry Contact Switch
Weight	3 oz.	Programming	PC Based Programming Kit
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	Ivory	Frequency Range	900 MHz
Operating Temperature	-4° - 140°F	Paging Addresses	1
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification