



WPT-1214 - Wireless 900 MHz Four-Button Pendant Transmitter



WPRP-1575

Key Features:

- Four Programmable ID's
- 300' - 1,000' Range (Increased Using Data Repeater)
- Transmission Indicator
- Long-life Single Lithium Battery
- Low Battery Alert
- Includes Key Chain

The **WPT-1214 Wireless 900MHz Four-Button Pendant Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4800** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

Each button generates a signal with its own specific activation code.

When any of the WPT-1214 buttons are pressed, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPT-1214 can generate an automated message to report low battery status. In addition, the WPT-1214 offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

Options, Accessories and Complementary Products:

Part Number	Description
WPRP-1575	Wireless 900 MHz Repeater

Specifications:

Dimensions	1.65" x 3" x 0.72" (W x H x D)	Activation Type	Momentary Switch
Weight	1.7 oz.	Programming	PC Based Programming Kit
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	Black	Frequency Range	900 MHz
Operating Temperature	32° - 140°F	Activation Codes	4
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification