



## VP-4 - Four-Line Alphanumeric Pager



The **VP-4 Four-Line Alphanumeric Pager** is designed to accommodate a wide variety of paging applications and environments.

The VP-4 supports 6 activation codes (ID's) for individual activation or membership activation in 5 separate groups. Creating groups provides the ability to activate multiple devices using a single transmission from a main wireless paging controller, such as the **VS4800** or **VNS5100**.

The VP-4 includes a plastic carrying case, lanyard and battery.

### Key Features:

- **Four-Line or Two-Line Alphanumeric Display Format**
- **Message Time Stamp**
- **Unread Message Reminder**
- **Low Battery Indication**
- **Adjustable LCD Contrast**
- **Backlight Display**
- **In-Range Indication**
- **Date and Time Display**
- **Vibrate and Tone Modes**

### Options, Accessories and Complementary Products:

Part Number	Description
VP-LC-4	Leather Case for VP-4 and VP-210

### Specifications:

Dimensions	2.8" x 1.9" x 0.7" (W x H x D)	Selectivity	Better than 65 db
Weight	1.6 oz.	Spurious Rejection	Better than 60 PPM
Power	One 1.5 V AAA Battery	Image Rejection	Better than 50 db
Color	Semi-Transparent Black	Stability	Better than 5 PPM
Operating Temperature	14° - 130°F	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Humidity	0% - 95%, Non-Condensing	Paging Format	POCSAG, Narrow Band
Alert Level	Minimum 75 db	Data Baud Rate	512, 1200 or 2400 BPS
Display Format	Four Lines with Up to 22 Characters Per Line Two Lines with Up to 16 Characters Per Line	Receiver Sensitivity	7u V/M
Activation Codes	6	Limited Warranty	One Year Parts and Labor

\*Specifications Are Subject to Change Without Notification

# VISIPLEX

## 877 918-7243

www.visiplex.com