



The WPT-02 Wireless UHF Pull Cord Transmitter is designed to send a pre-programmed text message directly to a

When the WPT-02 is reset to its normal position, a cancellation alert can be sent. In addition, the WPT-02 can generate an automated message to report low battery status. The WPT-02

*Note: A deep plastic single gang box is required for optimal signal

designated pager or LED display.

includes a pull cord and mounting hardware.

coverage. Metal box not recommended.

WPT-02 - Wireless UHF Pull Cord Emergency Transmitter











Key Features:

- Two Programmable Messages
- Sends Message Directly to a Pager
- 300' 1,000' Range (Increased Using Data Repeater)
- Transmission Indicator
- In-Wall Mount
- Surface Mount Installation Option (Recommended)
- Long-life Single Lithium Battery
- Low Battery Alert

Options, Accessories and Complementary Products:

Part Number	Description
VSPS-03	Programming Kit
WPRP-1/WPRP-2/WPRP-5	Data Repeater
WPA-1003	Deep Plastic Box for Surface Mount Installation

Specifications:

Dimensions	2.8" x 4.5" x 2.5" (W x H x D)	Activation Type/Call Cancel	Toggle
Weight	2.6 oz.	Signalling Time	2 - 4 Seconds
Power	Single 3V Lithium Battery	Stability	Better than 5 PPM
Color	White	Frequency	467.8000 MHz (Additional Frequencies Available)
Operating Temperature	32° - 140°F	Paging Format	POCSAG, 512 or 1200 BPS
Humidity	0% - 90%, Non-Condensing	Channel Spacing	12.5 KHz - Narrow Band
RF Power	10 mW	Activation Codes	3 (Call, Cancel & Low Battery)
Programming	PC Based Programming Kit	Limited Warranty	One Year Parts and Labor

^{*}Specifications Are Subject to Change Without Notification

