



WPT-EN1242 - Wireless Smoke Detector Transmitter



WPRP-EN5040

Key Features:

- One Pre-Programmed ID
- 300' - 1,000' Range (Increased Using Data Repeater)
- Two Long-life Lithium Batteries
- Ceiling Mount

The **WPT-EN1242 Wireless Smoke Detector Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4800** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

When the WPT-EN1242 detects smoke, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPT-EN1242 can generate an automated message to report low battery status. In addition, the WPT-EN1242 offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

***Note:** Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

Options, Accessories and Complementary Products:

Part Number	Description
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)

Specifications:

Dimensions	5.5" x 2.63" (W x D)	Activation Type	Smoke Detection
Weight	9.9 oz.	Programming	PC Based Programming Kit
Power	Two 3V Lithium Batteries	Transmit Format	Multi-Channel Spread Spectrum
Color	White	Frequency Range	900 MHz
Operating Temperature	0° - 140°F	Activation Codes	1
Humidity	0% - 95%, Non-Condensing	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification