



VNS2502 Mobile PA Paging Controller



The VNS2502 is a wireless voice & data controller that can be used as a mobile paging solution for emergency mass notification applications. The VNS2502 can wirelessly initiate live and pre-programmed voice messages, activate strobe lights and generate text alerts to alphanumeric LED displays.

When installed in a vehicle, the VNS2502 gives an on-site security personnel full control to notify and alert a specific zone or area mass notification, while in transit.

The AlertWave system mobile transmitters utilize a FCC approved paging bands and offers transmitter power options from 8 to 40 Watts to provide the right radio coverage to each facility.

The AlertWave system is fully modular, allowing you to start with a system that fits your immediate needs while maintaining the ability to add more wireless speakers, strobe lights, LED displays and sirens if needed.

Solutions for:

- *Universities*
- *Medical Centers*
- *Government Facilities*
- *Office Buildings*
- *Military Facilities*
- *Schools*
- *Financial Institutions*
- *Manufacturing Plants*

Features:

- *Mobile emergency control center*
- *Reduce confusion, injury and mass casualties in the event of emergency*
- *Improve personnel response time during emergency situations*
- *Wireless Public Address messaging*
- *Compact design for mobile uses*
- *Instant audible and/or silent visual alerts*
- *Require minimal training and easy to install*
- *Easy dashboard mounting*

Technical Specifications

VNS2502

PPM Alerts:	100 pre-programmed alphanumeric, tone or voice alerts that can be initiated from the unit keypad or over the phone.	Telephone:	Built-in PABX telephone interface for remote alert activation and PA announcements.
Database:	1000 device database and groups.	Display:	Two-Line green LCD Display with backlit.
RF Transmitter:	Internal 8W transmitter or external transmitter of up to 40W for complete radio coverage of large facilities.	Interface:	RS-232 port for PC programming and an integrated handheld microphone.
Software:	PC Windows based software package to program, control and backup the unit database.	Power:	Operates from a 12VDC 3A, AC or car power adaptor.
		Dimensions:	9.7" wide x 2.4" high x 5.5" deep, with dashboard mounting.



VNS2502 - Wireless Mobile Control Center