



## WPT-EN1260 - Wireless Motion Detector Transmitter



WPRP-EN5040

### Key Features:

- One Pre-Programmed ID
- 500' Range
- Long-life 3V Lithium Battery
- Wall Mount

The **WPT-EN1260 Wireless Motion Detector Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4800** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

When the WPT-EN1260 detects motion, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPT-EN1260 can generate an automated message to report low battery status. In addition, the WPT-EN1260 offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

**\*Note:** Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

### Options, Accessories and Complementary Products:

Part Number	Description
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)

### Specifications:

Dimensions	2.5" x 4.5" x 1.6" (W x H x D)	Activation Type	Motion Detection
Weight	9.9 oz.	Programming	PC Based Programming Kit
Power	1 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	Off-White	Frequency Range	900 MHz
Operating Temperature	0° - 140°F	Activation Codes	1
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor
Mounting Height	7-9 ft.		

\*Specifications Are Subject to Change Without Notification