



VP-PAD - Paddle Pager





The VP-PAD Paddle Pager is designed as an over-sized vibrating pager designed specifically for guests, visitors and patients in waiting areas and is an ideal solution for hospitals, doctor clinics, hotels, restaurants and more.

The VP-PAD supports 4 activation codes (ID's) for individual activation or membership activation in 3 separate groups. Creating groups provides the ability to activate multiple devices using a single transmission from a main wireless paging controller, such as the **VS4800** or **VNS5100**.

Key Features:

- One Button for Alert Disabling
- LED Call Indicator
- Large Custom Label Area
- Vibrate or Tone Only Pager

Options, Accessories and Complementary Products:

Part Number	Description	
VP-Pad-Charger	10-unit Coaster Charger with Batteries, Dimensions: 3.8" x 2.2" x 13.8" (W x H x D)	

Specifications:

The state of the s					
Dimensions	2.6" x 7.5" x 0.9" (W x H x D)	Selectivity	Better than 65 db		
Weight	4 oz.	Spurious Rejection	Better than 60 PPM		
Power	One 1.5 V AA Alkaline Battery, (Optional VP-Pad Charger)	Image Rejection	Better than 50 db		
Color	Red	Stability	Better than 5 PPM		
Operating Temperature	14º - 130ºF	Paging Format	POCSAG, Narrow Band		
Humidity	0% - 95%, Non-Condensing	Data Baud Rate	512 or 1200 BPS		
Alert Level	Minimum 65 db	Receiver Sensitivity	7u V/M		
Activation Codes	4	Limited Warranty	One Year Parts and Labor		
Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)				

^{*}Specifications Are Subject to Change Without Notification

