

[PROTECTIVE SLEEVING]

PET

Size	Nominal Diameter	Feet per spool	Price per foot	Price per spool
1/8"	3/32" to 1/4"	1000'	\$0.25	\$212.50
1/4"	1/8" to 7/16"	1000'	\$0.28	\$238.00
3/8"	3/16" to 5/8"	500'	\$0.45	\$191.25
1/2"	1/4" to 3/4"	500'	\$0.59	\$250.75
3/4"	1/2" to 1-1/4"	250'	\$0.93	\$197.63
1-1/4"	3/4" to 1-3/4"	250'	\$1.22	\$259.25
1-1/2"	1" to 2-1/2"	250'	\$1.60	\$340.00
1-3/4"	1-1/4" to 2-3/4"	200'	\$2.12	\$360.40
2"	1-1/2" to 3-1/2"	200'	\$2.73	\$464.10
2-1/2"	1-3/4" to 4-1/2"	200'	\$3.58	\$608.60

Flexo PET is braided from a 10 mil monofilament yarn of polyethylene terephthalate. It is especially useful in passive applications where flexibility, durability and economy are important considerations.

Available in black, red, orange, yellow, green, blue, violet, gray, white and clear. Custom colors are also available. (Some colors available in bright neon).

Operating Temperature 125°C




FR (Flame Retardant)

Size	Nominal Diameter	Feet per spool	Price per foot	Price per spool
1/8"	3/32" to 1/4"	1000'	\$0.30	\$255.00
1/4"	1/8" to 7/16"	1000'	\$0.33	\$280.50
3/8"	3/16" to 5/8"	500'	\$0.80	\$340.00
1/2"	1/4" to 3/4"	500'	\$0.80	\$340.00
3/4"	1/2" to 1-1/4"	250'	\$1.18	\$250.75
1-1/4"	3/4" to 1-3/4"	250'	\$1.65	\$350.63
1-3/4"	1" to 2-1/2"	200'	\$2.78	\$472.60
2"	1-1/2" to 3-1/2"	200'	\$3.48	\$591.60
2-1/2"	1-3/4" to 4-1/2"	200'	\$4.14	\$703.80

Flexo FR is braided from a 10 mil monofilament yarn of polyfyr polyester. It is recommended for applications where flame-resistance and durability are critical.

Available in Black with a white tracer & White with a black tracer.

Operating Temperature 125°C



[PROTECTIVE SLEEVING]

CC (Clean Cut)

Size	Nominal Diameter	Feet per spool	Price per foot	Price per spool
1/8"	1/8" to 1/4"	1000'	\$0.47	\$400.35
1/4"	5/32" to 7/16"	1000'	\$0.47	\$400.35
3/8"	3/16" to 5/8"	500'	\$0.79	\$335.75
1/2"	1/4" to 3/4"	500'	\$0.89	\$379.95
3/4"	5/8" to 1"	250'	\$1.13	\$239.91
1"	3/4" to 1-3/16"	250'	\$1.27	\$269.88
1-1/4"	3/4" to 1-1/2"	250'	\$1.60	\$340.00
1-1/2"	1-1/4" to 2"	250'	\$2.02	\$429.25

Flexo CC is braided from a 8 mil monofilament yarn of polyethylene terephthlate. It is especially useful in passive applications where flexibility, durability and economy are important considerations.

Fray resistant construction can be cut to length with scissors.

Available in black

Operating Temperature 125°C



HW (Heavy Wall)

Size	Nominal Diameter	Feet per spool	Price per foot	Price per spool
3/8"		500'	\$0.90	\$382.50
5/8"		250'	\$1.30	\$276.25
1"		250'	\$1.80	\$382.50
1-1/2"		250'	\$2.30	\$488.75
2"		200'	\$4.10	\$697.00
3"		100'	\$4.90	\$416.50
4"		100'	\$6.10	\$518.50



HW is braided from a 15 mil monofilament yarn of polyethylene terephthlate. It is especially useful in passive applications where flexibility, durability and abrasion resistance are important considerations.

Available in black.

Operating Temperature 125°C

[PROTECTIVE SLEEVING]

FLEXO WRAP®

Size	Hook and Loop Diameter	Feet per spool	Price per foot	Price per spool
1/2"	1/2"	100'	\$3.20	\$272.00
3/4"	3/4"	100'	\$3.66	\$311.00
1-1/4"	1-1/4"	100'	\$5.08	\$432.00
2"	2"	100'	\$5.55	\$472.00

FLEXO WRAP® (FW) is braided from 10 mil PET and FR monofilaments with an attached nylon hook and loop fastener.

FLEXO WRAP® (FW) hook and loop expandable sleeving is designed for quick and easy bundling and protection of wire, cable and hose assemblies. This design gives easy access for harness rework without disrupting existing connections, or routing sleeving over the entire bundle.

Since FLEXO WRAP® “wraps around” assemblies, it is an excellent choice for securing existing systems as well as new assemblies. Unlike spiral or tie-on wrapping devices, FLEXO WRAP® covers the entire assembly, protecting it from cuts, abrasion, high temperatures, chemicals, and UV light. Once installed, FLEXO WRAP® conforms to various shapes and sizes, securing them snugly within the bundle.

No scissors, cut with hot knife.

Available in black
Special order colors Beige and Gray

Operating Temperature -102°F to 257°F



DURA WRAP®

Size	Hook and Loop Diameter	Feet per spool	Price per foot	Price per spool
1"	1"	50'	\$6.75	\$286.88
2"	2"	50'	\$9.50	\$403.75
3"	3"	25'	\$12.60	\$267.75
4"	4"	25'	\$15.70	\$333.63

DURA WRAP® is the answer to organizing and controlling wires, cables and hoses that are subjected to constant and extreme use. The flexible sleeve is made from tightly woven ballistic Nylon with an aggressive, industrial strength Velcro® closure. DURA WRAP® is used on wires to keep them together and on hoses and cables to keep them from ruining expensive finished surfaces.

Operating Temperature -102°F to 257°F

Available in black.



heatshrink.com™

We believe the above information to be correct and assume no liability for errors.

[PROTECTIVE SLEEVING]

SPLIT BRAID

Size	Feet per spool	Price per spool
1/8"	400'	\$193.80
1/4"	200'	\$181.90
1/2"	150'	\$209.10
3/4"	100'	\$176.80
1"	100'	\$246.50
1 1/2"	75'	\$355.09
2"	50'	\$332.78



The 10 mil SPLIT BRAID is lightweight, quiet and flexible. The 25% edge overlap (at nominal diameter) allows complete coverage even around inline plugs, connectors and splices.

Available in black.

Operating Temperature 125°C

REFLEX™ Reflective Safety Braid

Size	Nominal Diameter	Feet per spool	Price per foot	Price per spool
1/4"	3/16" to 3/8"	1,000'	\$2.35	\$1,997.50
1/2"	3/8" to 7/8"	500'	\$3.55	\$1,508.75



Open mesh construction allows water to dissipate • Safety at night • Light weight • Visible at 360 feet • High-tech braided look • 3M® Ultra Reflective Process • Easily integrated • Allows your wires and cables to reflect in the dark • REFLEX™ is 1500 times brighter at night than white.

Braided with 25% 3M® Ultra Reflective Fiber and 75% Rugged PET Monofilament.

This braid provides a criss-cross braided design which when hit with light reflects back to the light source

Available in black or clear.

Bench Mount Hot Knife

110 volt A.C.



This tool enables the operator to draw the sleeving down across the knife blade - under tension. Both hands are then free to manipulate the sleeving and to seal and flare the ends. Tool should be used in well ventilated areas.







- Warms up in less than 30 seconds
- Will cut through a 1" nylon line in ten seconds

Price
\$115.00

heatshrink.com™

We believe the above information to be correct and assume no liability for errors.

[PROTECTIVE SLEEVING]

	Clean Cut FR	Scissor cut for field installation, will not support combustion.
	Liquid Wrap	Stylish fluid protection for wires and cables.
	F6 FR	Flexible semi-rigid split sleeving will not support combustion.
	Flexo Wrap FR	Easy on, easy off access. Will not support combustion.
	Tightweave FR	Tight braid for fuller coverage.
	Flexo Halar	Very low outgassing, self extinguishing UL-2024 Plenum rated sleeving.
	Teflon	High temp stable, abrasion resistant, low outgassing.
	Flexo PPS	Ultra lightweight, high temp tolerant and virtually impervious to chemical degradation.
	Kevlar	Stronger than steel, soft and pliable.
	Vectran	A unique combination of properties for demanding applications.
	Studio Key Sleeve	Keyable sleeve for special effects professionals.
	Flexo Mounting System	The ultimate termination solution for flexo sleeving.
	Dura-Race	Abrasion protection for high traffic carpeting with easy on, easy off hook closure.
	Non Skid	Increased friction on smooth surfaces minimizes slipping and accidents.
	Nylon Monofilament	Reliability recognized around the world.
	Nylon Multifilament	Full coverage, soft supple, strong and attractive.
	Mylar	Lightweight, economical metallic alternative.
	Chrome	The look of stainless steel braid with an upside.
	Chrome XC	The same as Chrome with more coverage.
	Flexo 6 mil	High density fine thread sleeving.
	Flexo Thin	Ultra thin for specialized for fiber applications.
	Carbon Fiber	Carbon fiber sleeve for high strength tubular structures.

call for more information and pricing on these Techflex products

[PROTECTIVE SLEEVING]



Flexo Noise Reduction	Self fitting protective oversleeve.
F6 Quiet	Nostalgic look and feel! modern day performance.
Metal Braid	Tinned copper sleeve for shielding, grounding, and decoration.
Stainless Steel	Braided stainless steel, pre-rounded for installation ease.
Stainless Steel XC	Same as Stainless Steel but with more coverage.
Flexo Shield	Lightweight shielded expandable sleeving.
Flexo Conductive	Conductive carbon infused nylon for static protection and shielding
Insultherm	Resin saturated fiberglass, protects up to 1200° F.
Insultherm Tru-fit	Heat treated, fray resistant fiberglass sleeving.
Insultherm Ultraflexx	Braid fiberglass protects up to 1200° F.
Insultherm Ultraflexx Pro	Heavy wall fiberglass protects up to 1200° F.
Insultherm Sleeves	Double wall fiberglass sleeves protect wires and spark plug boots to 1200° F.
Header Wrap	Vermiculite coated fiberglass wrap withstands heat up to 1200° F.
Header Wrap SI	Silica wrap withstands continuous heat up to 2000° F.
Volcano Wrap	Woven Volanic rock tape withstands heat up to 1500° F.
Silica Sleeve	Easy slip on installation protects up to 1800° F.
Therma Shield T6	Flexible thermal reflective wrap deflects radiant heat upto 1400° F.
Therma Shield	Reflective aluminized surface bonded to insulating fiberglass in 4 styles.
Nomex	Soft, pliable flame protection to 662° F.
Weld Wrap	Protects vulnerable welding hoses from catastrophic failure.
Fireflex	Silicone jacketed fiberglass resists heat, abrasion and moisture.
Fireflex Aero	High temperature sleeve AS1072

call for more information and pricing on these Techflex products