



## WPT-EN1210W - Universal Wireless 900 MHz Transmitter



### Key Features:

- One Pre-Programmed ID
- 300' - 1,000' Range (Increased Using Data Repeater)
- Built-in Magnetic Switch and Dry Contact Closure
- Long-life Single Lithium Battery
- Low Battery Alert
- Wall, Door or Surface Mount

The **WPT-EN1210W Universal Wireless 900MHz Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4800** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

The WPT-EN1210W includes a magnetic switch sensor that can be installed on doors or windows to generate an automated alert when the door or window is opened or closed (normally open or normally closed).

When the WPT-EN1210W internal magnetic sensor is activated by the included magnet, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

When the WPT-EN1210W is reset to its normal status, a cancellation alert can be sent.

The WPT-EN1210W can generate an automated message to report low battery status. In addition, the WPT-EN1210W offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

The WPT-EN1210W includes mounting hardware.

**\*Note:** Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

### Options, Accessories and Complementary Products:

Part Number	Description
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)

### Specifications:

Dimensions	1.75" x 3.5" x 0.9" (W x H x D)	Activation Type	Magnetic / Dry Contact Switch
Weight	3 oz.	Programming	PC Based Programming Kit
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	Ivory	Frequency Range	900 MHz
Operating Temperature	-4° - 140°F	Activation Codes	1
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor

\*Specifications Are Subject to Change Without Notification