



TS5263 - Wireless Synchronized Digital Elapsed Timer



TS-OPT-012



TS-ACC-002



TS-ACC-003

Key Features:

- Viewing Distance of 100'
- Automatic Daylight Saving Time Adjustment
- Non-Glare Acrylic Lens
- Quick Correction for Time Change (1-3 Minutes)
- Flush Mount, Does Not Require Back Box
- AC Power Operated
- AM/PM Indicator

Options, Accessories and Complementary Products:

Part Number	Description
TS-OPT-009	Wireless Synchronization
TS-OPT-012	Infrared Remote Control
TS-ACC-002	Dual Face Bracket for Digital Clock - Wall Mount
TS-ACC-003	Dual Face Bracket for Digital Clock - Ceiling Mount

Specifications:

Dimensions	18.23" x 6.22" x 1.5" (W x H x D)	Digit Count, Size & Color	6 Digits, 2.5" High, Red
Weight	4 lbs.	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Power	12V DC / 2A (Using 100-240V AC)	Paging Format	POCSAG, Narrow Band
Operating Temperature	17° - 140°F	Synchronization	Instantaneous
Humidity	0% - 95%, Non-Condensing	Receiver Sensitivity	10u V/M
Frame and Lens	Black Aluminum Frame, Red Diffused Acrylic Lens	Limited Warranty	One Year Parts and Labor
Viewing Distance	100 ft.		

*Specifications Are Subject to Change Without Notification

The TS5263 Wireless Synchronized Digital Elapsed Timer is designed with a highly visible 2.5" LED four-digit display for the hours/minutes and a 1.8" LED two-digit display for the seconds.

The TS5263 receives a wireless time signal transmitted daily by a main wireless paging controller, such as the VS4800. The TS5263 uses the time signal to automatically adjust itself, if necessary, to ensure accurate and synchronized time throughout the entire facility.

The TS5263 matches a wide variety of applications and provides years of maintenance-free service.

The TS5263 comes with a wired wall plate controller which can be replaced by the TS-OPT-012 infrared remote control option.

