



WPT-EN1235 - Wireless 900 MHz One-Button Pendant Transmitter





WPRP-FN5040

Key Features:

- One Pre-Programmed ID
- 300' 1,000' Range (Increased Using Data Repeater)
- Transmission Indicator
- Long-life Single Lithium Battery
- Low Battery Alert
- Includes Belt Clip

The WPT-EN1235 900MHz One-Button Pendant Transmitter is designed to be used with a main wireless paging controller, such as the VS4800 or VNS5100. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

When the WPT-EN1235 button is pressed, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPT-EN1235 can generate an automated message to report low battery status. In addition, the WPT-EN1235 offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

*Note: Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

Options, Accessories and Complementary Products:

Part Number	Description	
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)	

Specifications:

·					
Dimensions	1.6" x 3.1" x 1" (W x H x D)	Activation Type	Momentary Switch		
Weight	1.7 oz.	Programming	PC Based Programming Kit		
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum		
Color	Black	Frequency Range	900 MHz		
Operating Temperature	32° - 140°F	Activation Codes	1		
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor		

^{*}Specifications Are Subject to Change Without Notification

