



MFS-8 MAC Filtering Network Switch

Protect the network by preventing audio streams from slowing it down. Eight ports. Conventional switches installed “downstream” from MFS-8 are equally protected.

Key Features

- Eight (8) ports

Specifications

Layer 2 MAC Filtering Configuration: Instant - Pre-configured at factory

Network Switching Hub: Eight 10/100 Ethernet ports

LAN: One 10/100 Ethernet port

Power: 12V External Power Supply

Size: 9.8” x 1.5” x 4.9” (W x H x D)

Weight: 0.78 lbs



PoE-1 Ethernet Power Injector

Use the PoE-1 in place of a PoE switch (like the MFSPOE-8) to provide power to PoE devices via Ethernet cable. Powers IP cameras, keypads, in-wall touchscreens, etc.

Key Features

- Compact design with detachable power cord
- Includes power cord

Specifications

Power: 100-240V, 0.6A, 50-60Hz

Size: 5” x 1.5” x 2.5” (W x H x D)

Weight: 0.20 lbs



PIR-1 IR Code Learning Device

Use the PIR-1 to record and transmit codes from legacy IR remote controls when upgrading to a Total Control system.

Key Features

- Compact design
- Includes batteries and USB cable

Specifications

Power: Powered via USB connector and/or two AAA batteries (included)

Size: 1.875” x 5.25” x .75” (W x H x D)

Weight: 0.35 lbs