



CFLT Series 4200 Simplex Cartridge Filters

PP OR PVDF (SERIES 5200)

KEY FEATURES

- PP or PVDF Housing
- No Rust, Corrosion or Contamination
- Rated to 150 PSI
- In-Line or Loop Flow
- Hand-Removable Cover
- Simplex or Duplex Designs

CARTRIDGE TYPES

- Hayward® HC 16" cellulose nominally rated 5 and 25 microns
- Hayward PF 20" and 30" PP absolutely rated at 1, 5 or 10 microns

SELECTION CHART

HOUSING	HC CARTRIDGE	MAX FLOW RATE	PF CARTRIDGE	MAX FLOW RATE
CFLT4201	One 16"	50 GPM	N/A	N/A
CFLT4202	Two 16"	100 GPM	Five 30"	100 GPM
CFLT4203	N/A	N/A	Five 20"	50 GPM

Heavy-Duty Filter Bags

PP FELT OR MESH
1 TO 800 MICRON RATINGS

Your filtration process is only as effective as your filter bag. Don't compromise it with anything less than a Hayward precision quality filter bag that's guaranteed to fit your Hayward filter vessel.

KEY FEATURES

- Thermoplastic Ring Seal
- Heavy Duty Sewn or Welded Construction
- Silicone-Free

OPTIONS

- Custom Filter Bags for Most Any Application



SELECTION CHART

MATERIAL	CONSTRUCTION	SEAL MATERIAL/TYPE	MICRON RATINGS
PP Needle Felt	Welded	PP SENTINEL®	1, 5, 10, 25, 50, 100, 200
PP Needle Felt	Sewn	PP SNAP-RING™	1, 5, 10, 25, 50, 100, 200
PP Mesh	Sewn	PP SNAP-RING	400, 600, 800