ON-PREMISES LAUNDRY HARDMOUNT SCN040KV

FEATURES & BENEFITS

- Advanced water protection alerts owners if the washer has a stuck drain, slow drain condition or leaking inlet valve, which helps conserve water.
- Rugged door handle and new lock mechanism ensure easy opening and closing and reliable locking
 — no more door lock error codes.
- New dual triple-lip seals and a stainless steel sleeve around the trunnion, deliver the strongest line of defense in protecting the bearings against the damaging effects of moisture.
- Four-compartment chemical dispenser adds chemicals at the right time, automatically saving staff time. The new dispenser design eliminates over-sudsing conditions. Four external supply signals also are included on Quantum Gold models.



PRODUCT SPECIFICATIONS

Width 30 5/8" 39 3/4" Height 47 1/4" Cylinder Diameter 26 1/4" Cylinder Depth 20 1/4" Cylinder Volume 6.34 cu. ft. Door Opening Size 16 1/4" Door Bottom to Floor 14 1/2" Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" A 13/16" A 13/16" A 13/16" A 13/16" A 13/15/50/60-3 N 440-480/50/60/3 Celectric heat) P 380-415/50/60/3 Net Weight 592 lb Shipping Weight 54 3/4" Shipping Depth 44 5/8" Shipping Height 56 3/4" Shipping Height 56 3/4"			SCN040KV
Depth 39 3/4" Height 47 1/4" Cylinder Diameter 26 1/4" Cylinder Depth 20 1/4" Cylinder Volume 6.34 cu. ft. Door Opening Size 16 1/4" Door Bottom to Floor 14 1/2" Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X Voltage/Hz/Phase X Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Depth 44 5/8" Shipping Height 56 3/4"	Capacity		40 lb
Height 47 1/4" Cylinder Diameter 26 1/4" Cylinder Depth 20 1/4" Cylinder Volume 6.34 cu. ft.	Width		30 5/8″
Cylinder Diameter	Depth		39 3/4"
Cylinder Depth 20 1/4" Cylinder Volume 6.34 cu. ft. Door Opening Size 16 1/4" Door Bottom to Floor 14 1/2" Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X Voltage/Hz/Phase X Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Depth 44 5/8" Shipping Height 56 3/4"	Height		47 1/4″
Cylinder Volume 6.34 cu. ft. Door Opening Size 16 1/4" Door Bottom to Floor 14 1/2" Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs Voltage/Hz/Phase X 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N Net Weight 592 lb Shipping Weight 620 lb Shipping Depth 44 5/8" Shipping Height 56 3/4"	Cylinder Diameter		26 1/4"
Door Opening Size	Cylinder Depth		20 1/4"
Door Bottom to Floor 14 1/2" Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X Voltage/Hz/Phase Q Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Height 56 3/4"	Cylinder Volume		6.34 cu. ft.
Wash Speeds 46 RPM Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X Voltage/Hz/Phase X Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Depth 44 5/8" Shipping Height 56 3/4"	Door Opening Size		16 1/4″
Extract Speed 733 RPM Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X 200-208/220-240/50/60/1/3 Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Door Bottom to Floor		14 1/2"
Distribution Speed 82 RPM Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X 200-208/208-240/50/60/1/3 Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Wash Speeds		46 RPM
Extract G-Force 200 Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Motor Size 2 HP Electrical Specs Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Extract Speed		733 RPM
Water Inlet 2 @ 3/4" Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X Voltage/Hz/Phase Q Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Distribution Speed		82 RPM
Drain Diameter 1 @ 3" Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X 200-208/208-240/50/60/1/3 Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Extract G-Force		200
Drain Height To Floor 4 13/16" Motor Size 2 HP Electrical Specs X 200-208/220-240/50/60/1/3 Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Water Inlet		2 @ 3/4"
Motor Size 2 HP Electrical Specs	Drain Diameter		1 @ 3"
Continue	Drain Height To Floor		4 13/16"
Voltage/Hz/Phase Q 200-208/220-240/50/60/3 (electric heat) P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Motor Size		2 HP
P 380-415/50/60-3 N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Electrical Specs Voltage/Hz/Phase	Χ	200-208/208-240/50/60/1/3
N 440-480/50/60/3 Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"		Q	200-208/220-240/50/60/3 (electric heat)
Net Weight 592 lb Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"		Р	380-415/50/60-3
Shipping Weight 620 lb Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"		Ν	440-480/50/60/3
Shipping Width 34 1/4" Shipping Depth 44 5/8" Shipping Height 56 3/4"	Net Weight		592 lb
Shipping Depth 44 5/8" Shipping Height 56 3/4"	Shipping Weight		620 lb
Shipping Height 56 3/4"	Shipping Width		34 1/4"
11 0 0	Shipping Depth		44 5/8"
Agency Approvals cETLus, CE	Shipping Height		56 3/4"
	Agency Approvals		cETLus, CE



QUANTUM GOLD OPL CONTROL

Quantum Gold offers a total of 30 programmable cycles as well as 30 programmable water levels that enable you to adjust water use in every cycle step. PC/PDA programming and audit data retrieval save time, as do advanced diagnostics. Quantum Gold machines feature a maximum extraction speed of 200 G-force.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO#9001:2000.

Printed in the U.S.A.

speedqueen.com

