

TECHNICAL SPECIFICATIONS

CLAYTON STEAM GENERATORS:

- * **SAVE FUEL**
The unique counter flow, controlled flow design provides higher fuel to steam efficiencies than traditional boilers.
- * **ARE SAFE FOR PERSONNEL & EQUIPMENT**
The Clayton units inherently eliminate the potential for hazardous steam explosions due to their smaller physical size and low water volume.
- * **PROVIDE RAPID RESPONSE**
With low water volume and physical size, Clayton units can respond very quickly to load changes
- * **PROVIDE FAST START-UP AND LOAD RESPONSE**
The units will provide full output from a cold start within ten minutes, without thermal stress.
- * **ARE COMPACT AND LIGHTWEIGHT**
The Clayton design typically occupies one-third of the floor space and is 75% lighter than a conventional boiler.
- * **ENSURE HIGH QUALITY STEAM**
Provide greater than 99.5% quality steam.
- * **AFFORD FUEL VERSATILITY**
Natural gas, propane, light or heavy oil burners are available or in combination.
- * **HAVE ADVANCED CONTROLS**
Programmable Logic Controllers (PLC) are standard for accurate and reliable operation.
- * **ARE AVAILABLE WITH LOW NOx**
Industry leading Low NOx burners are available to meet strict environmental regulations.
- **ARE BACKED BY** *Fast, Expert Factory-Direct service that is available 24 hours per day throughout the U.S., Canada, Mexico, Europe, Asia and service distributors worldwide.*



MODEL E704
STEAM GENERATOR
700 BHP

CLAYTON STEAM GENERATOR

SPECIFICATIONS

MODEL E704

	MODEL E704 Standard	MODEL SE704 with Super Economizer	MODEL EG704-FMB with Low NOx Burner	MODEL SEG704-FMB with Low NOx Burner and Super Economizer
BOILER HORSEPOWER	700	700	700	700
HEAT INPUT, BTU/hr				
Oil	28,231,928	27,247,093	NA	NA
Gas	28,576,220	27,567,647	28,929,012	27,567,647
NET HEAT OUTPUT, BTU/hr	23,432,500	23,432,500	23,432,500	23,432,500
EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam)	24,150 lbs/hr	24,150 lbs/hr	24,150 lbs/hr	24,150 lbs/hr
DESIGN PRESSURE (see note 1)	65 - 500 psig	65 - 500 psig	65 - 500 psig	65 - 500 psig
STEAM OPERATING PRESSURE (determined by design pressure)	60 - 450 psig	60 - 450 psig	60 - 450 psig	60 - 450 psig
OIL CONSUMPTION	200.8 gph	193.8 gph	NA	NA
at maximum steam output (see note 2)				
GAS CONSUMPTION	28,576 cfh	27,568 cfh	28,929 cfh	27,568 cfh
at maximum steam output (see note 3)				
BURNER CONTROLS				
modulating	5 to 1 Turndown	5 to 1 Turndown	4 to 1 Turndown	4 to 1 Turndown
EFFICIENCY				
oil-fired efficiency %	83%	86%	NA	NA
gas-fired efficiency %	82%	85%	81%	85%
ELECTRIC MOTORS, HP				
design pressure 15-300 psig	Blower 60 Pump 40	Blower 60 Pump 40	Blower 75 Pump 40 Cooling 7.5	Blower 75 Pump 40 Cooling 7.5
design pressure 301-500 psig	Blower 60 Pump 50	Blower 60 Pump 50	Blower 75 Pump 50 Cooling 7.5	Blower 75 Pump 50 Cooling 7.5
ELECTRIC FLA, based on 460 V (see note 4)				
design pressure 15-300 psig	155	155	190	190
design pressure 301-500 psig	170	170	205	205
GAS SUPPLY PRESSURE REQUIRED	5 to 10 psig	5 to 10 psig	5 to 10 psig	5 to 10 psig
ATOMIZING AIR REQUIRED (see note 5)				
Capacity	30 scfm	30 scfm	N/A	N/A
Minimum pressure	70 psig	70 psig	N/A	N/A
AIR SUPPLY REQUIRED (FMB -see note 6)	N/A	N/A	5 scfm @ 3 to 150 psig	5 scfm @ 3 to 150 psig
WATER SUPPLY REQUIRED	3,710 gph	3,710 gph	3,710 gph	3,710 gph
HEATING SURFACE	1,523 sq.ft.	1,701 sq.ft.	1,523 sq.ft.	1,701 sq.ft.
EXHAUST STACK DIAMETER, o.d.	35.75 in.	35.75 in.	35.75 in.	35.75 in.
APPROXIMATE OVERALL DIMENSIONS				
length	141 in.	141 in.	160 in.	160 in.
width	140 in.	140 in.	149 in.	149 in.
height	205 in.	215 in.	205 in.	215 in.
WEIGHT				
installed - wet	28,535 lbs	32,244 lbs	28,835 lbs	32,544 lbs
shipping	24,500 lbs	27,800 lbs	24,800 lbs	28,100 lbs
FW pump skid	2,400 lbs	2,400 lbs	2,400 lbs	2,400 lbs

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2.

5) Atomizing air required for oil burner.

6) Compressed air required for FMB.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

Europe, Africa & Middle East Headquarters
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service