ON-PREMISES LAUNDRY TUMBLE DRYER STT30

PRODUCT SPECIFICATIONS

Cabinet Dimensions	
Capacity	2 @ 30 lb
Width	31 1/2"
Depth	42 7/8"
Height	76 1/4"
Cylinder Diameter	30"
Cylinder Depth	26"
Cylinder Volume	10.6 cu.ft.
Door Opening Size	22 5/8"
Energy Data	
Gas Models - Per Pocket	73,000 Btu/hr
Steam Models - 100 psi	111,000 Btu/hr
Electric Models	21 kW
Connections	
Gas	1/2" NPT
Plumbing Connections - Steam	3/4" NPT
Air Outlet	8″
Motor	
-an	1/4 - 1/4 HP
Cylinder	N/A
Airflow	
Airflow	400 cfm
Shipping	
Net Weight	Gas/Steam: 544 lb Electric: 544 lb
Shipping Weight	Gas/Steam: 582 lb Electric: 582 lb
Shipping Width	32 1/2"
Shipping Depth	47"
Shipping Height	81″
Agency Approvals	
Gas Models	CSA, CE
Electric and Steam Models	CSA, CE

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO#9001:2000.


FEATURES & BENEFITS

- Fast drying performance.
- Concentrated airflow pattern and sealed cylinder rims ensure maximum air utilization and energy savings.
- Large, easy to clean lint compartment.
- Fewer moving parts mean fewer maintenance problems and less wear.
- High performance heater box increases energy efficiency, reduces drying times and provides more comfortable operating environment.



AVAILABLE CONTROLS

ControlDual Digital



Description

Set drying time, temperature and cool down. Features include one touch cycle repeat, automatic extended tumble and large digital countdown display.

ELECTRICAL SPECIFICATIONS

Gas and Steam	
Voltages	Amps
120/208-240/60/1	16.0/8.0
200-208/240/60/3	6.4/6.4
460-480/60/3	3.3

Electric		
Voltages	Amps	
200-208/60/3	124	
208/60/1	216	
240/60/1	188	
240/60/3	108	
380/60/3	66	
460-480/60/3	54	

