

Technical Specifications

The Next Generation of Clayton Steam Generators

Available in the following configurations:

- Standard configuration for most installations.
- Super Economizer (SE) for increased efficiency.
- Low NOx Fiber Metal Burner (FMB) for NOx levels below 12 ppmv.
- Step-fired and fully modulating burners.
- Fuel Options: Natural Gas, Propane, #2 Fuel Oil, Biogas and Hydrogen



The *SigmaFire*™:

- **SAVES FUEL**
The unique counter flow design provides higher fuel-to-steam efficiency than traditional boilers.
- **IS SAFE FOR PERSONNEL AND EQUIPMENT**
Inherently safe, the Clayton design eliminates hazardous steam explosions.
- **PROVIDES RAPID RESPONSE**
The Clayton design responds rapidly to sudden or fluctuating load demands.
- **STARTS FAST**
The Clayton design will provide full output from a cold start within five minutes, without thermal stress.
- **IS COMPACT AND LIGHTWEIGHT**
The Clayton design typically occupies one-third of the floor space and weighs 75% less than a traditional boiler.
- **ENSURES HIGH QUALITY STEAM**
Clayton offers a 99.5% quality separator to minimize moisture in the steam.
- **OFFERS ADVANCED CONTROLS**
Digital controllers, PLC's and a linkage-less servo controlled burner management system is available.
- **INCLUDES OUTSTANDING SUPPORT**
Every Steam Generator is backed by Clayton factory direct sales and service plus full service feedwater treatment.



SigmaFire™ 200 BHP
Steam Generator

SPECIFICATIONS

MODEL SF200

| | | MODEL SF200 Standard | MODEL SF200-SE with Super Economizer | MODEL SF200-FMB with Low NOx FMB Burner | MODEL SF200-SE-FMB with Low NOx FMB Burner and Super Economizer |
|---|-----|-------------------------|---|--|---|
| BOILER HORSEPOWER | | 200 | 200 | 200 | 200 |
| HEAT INPUT, BTU/hr | Oil | 8,066,265 | 7,784,884 | NA | NA |
| | Gas | 8,164,634 | 7,876,471 | 8,265,432 | 7,876,471 |
| NET HEAT OUTPUT, BTU/hr | | 6,695,000 | 6,695,000 | 6,695,000 | 6,695,000 |
| EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam) | | 6,900 lbs/hr | 6,900 lbs/hr | 6,900 lbs/hr | 6,900 lbs/hr |
| DESIGN PRESSURE (see note 1) | | 15 - 500 psig | 15 - 500 psig | 15 - 500 psig | 15 - 500 psig |
| STEAM OPERATING PRESSURE (determined by design pressure) | | 13 - 450 psig | 13 - 450 psig | 13 - 450 psig | 13 - 450 psig |
| OIL CONSUMPTION at maximum steam output (see note 2) | | 57.4 gph | 55.4 gph | NA | NA |
| GAS CONSUMPTION at maximum steam output (see note 3) | | 8,165 cfh | 7,876 cfh | 8,265 cfh | 7,876 cfh |
| BURNER CONTROLS | | | | | |
| step-fired | | 100% / 50% / Off | 100% / 50% / Off | N/A | N/A |
| modulating (see note 4) | | 5 to 1 Turndown | 5 to 1 Turndown | 4 to 1 Turndown | 4 to 1 Turndown |
| EFFICIENCY | | | | | |
| oil-fired efficiency % | | 83% | 86% | NA | NA |
| gas-fired efficiency % | | 82% | 85% | 81% | 85% |
| ELECTRIC MOTORS, HP | | Blower Pump | Blower Pump | Blower Pump Cooling | Blower Pump Cooling |
| design pressure 15-300 psig | | 10 7.5 | 10 7.5 | 15 7.5 3 | 15 7.5 3 |
| design pressure 301-500 psig | | 10 10 | 10 10 | 15 10 3 | 15 10 3 |
| ELECTRIC FLA, based on 460 V (see note 5) | | | | | |
| design pressure 15-300 psig | | 25 | 25 | 32 | 32 |
| design pressure 301-500 psig | | 28 | 28 | 35 | 35 |
| GAS SUPPLY REQUIRED | | 2 psig | 2 psig | 2 psig | 2 psig |
| AIR SUPPLY REQUIRED (FMB - see note 6) | | NA | NA | 5 scfm @ 3 to 150 psig | 5 scfm @ 3 to 150 psig |
| WATER SUPPLY REQUIRED | | 1,060 gph | 1,060 gph | 1,060 gph | 1,060 gph |
| HEATING SURFACE | | 269 sq.ft. | 314 sq.ft. | 269 sq.ft. | 314 sq.ft. |
| EXHAUST STACK DIAMETER, o.d. | | 17.88 in. | 17.88 in. | 17.88 in. | 17.88 in. |
| APPROXIMATE OVERALL DIMENSIONS | | | | | |
| length | | 81 in. | 81 in. | 85 in. | 85 in. |
| width | | 80 in. | 80 in. | 101 in. | 101 in. |
| height | | 106 in. | 112 in. | 106 in. | 112 in. |
| WEIGHT | | | | | |
| installed - wet | | 5,317 lbs | 5,867 lbs | 5,397 lbs | 5,947 lbs |
| shipping | | 4,750 lbs | 5,150 lbs | 4,830 lbs | 5,230 lbs |

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) On dual fuel units only gas fired is modulating, oil fired is step fired. Switching fuels requires a manual change of burners

5) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2.

6) Compressed air required for FMB only.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

Europe, Africa & Middle East Headquarters
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service