

SureFlo Soap Dispensing System



BOBRICK SureFlo® SOAP SYSTEM

SureFlo SOAP SYSTEM CABINET

Accommodates one 12-liter (13,000 handwashes) SureFlo Soap Cartridge. Cabinet is equipped with a concealed 2-liter (2,000 handwashes) soap reservoir. Cabinet is constructed of type 304 stainless steel. Door has satin finish and tumbler lock, keyed like other Bobrick washroom accessories. Cabinet is equipped with Low Soap Indicator (LSI) Light. Cabinet is mounted under lavatory countertop on left or right side walls, or rear wall. Includes tubing and connectors. Cabinet furnished with one 12-liter cartridge of Bobrick SureFlo Soap. Cabinet 10" W, 15 1/4" H in front, 16 1/2" H in rear, 18 5/8" D (255 x 385-420 x 475mm). Patented.

B-830.12 Soap System Cabinet with one 12-liter cartridge of Pink Lotion SureFlo Soap.

B-830.13 Soap System Cabinet with one 12-liter cartridge of Premium Gold SureFlo Soap.

B-830 SOAP DISPENSER SOAP PUMP (360° FREE TURNING), MOUNTING SHANK KITS

One kit required for each lavatory-mounted soap dispenser. Also requires one 830-341 Connector Kit for each soap dispenser.

PART NO.	SOAP PUMP, MOUNTING SHANK KITS
830-359	4" (100mm) Spout Length, Bright-Polished Stainless Steel (B-822)
830-372	6" (150mm) Spout Length, Bright-Polished Stainless Steel (B-8226)

Note: Maximum Countertop Mounting Thickness 1 3/4" (45mm). For thicker countertops up to 4 3/4" (110mm) order Bobrick part number 822-402.

830-341 SureFlo CONNECTOR KITS FOR B-830 SERIES SOAP DISPENSERS

One kit required for each B-830 Series Soap Dispenser. Includes vandal-resistant tubing and connectors for installation of B-830 SureFlo Soap Dispensing System.

HOW TO SPECIFY/ORDER:

B-830.12, or **B-830.13** Soap System Cabinet.

830-359 or **830-372** Soap Dispenser Soap Pump, Mounting Shank Kit.

830-341 Connector Kit. One kit required for each soap dispenser.

SureFlo SOAP SYSTEM SOAP CARTRIDGES

Formulated especially for Bobrick B-830 Series Lavatory-Mounted Soap Dispenser Systems.

 **B-81312** Premium Gold Soap, 12-liter (13,000 handwashes)

 **B-81212** Pink Lotion Soap, 12-liter (13,000 handwashes)

WARRANTY

Only Bobrick SureFlo Soaps should be used in B-830 Series Lavatory-Mounted Soap Dispenser SureFlo Soap System. Use of any other soap will void the warranty provided for the B-830 Series Soap Dispensers used in the SureFlo Soap System. See page 40 for warranties and limitations on Bobrick's SureFlo Soap System.

Lavatory Mounted Soap Dispensers



B-826 SERIES LIQUID SOAP DISPENSER



NEW

B-8263 SERIES FOAM SOAP DISPENSER



B-822 SERIES SOAP DISPENSERS

For ease of maintenance and labor savings • Vandal-resistant locking cover and free-turning spout • Corrosion-resistant • Bright-polished spout, cover and escutcheon • High-impact-resistant ABS body and shank • Shatter-resistant polyethylene container • Patented



B-822



B-8221

LIQUID & LOTION SOAPS, AND SYNTHETIC DETERGENT DISPENSERS:

MODEL NUMBER	CAPACITY	SPOUT LENGTH	MAX. MTG. THICKNESS
B-822	34-fl oz (1.0-L)	4" (100mm)	4" (100mm)
B-8221	20-fl oz (0.6-L)	4" (100mm)	1" (25mm)
B-8226	34-fl oz (1.0-L)	6" (150mm)	4" (100mm)
B-82216	20-fl oz (0.6-L)	6" (150mm)	1" (25mm)

IMPORTANT NOTE:

All Bobrick B-822 Series Soap Dispensers are designed to dispense commercially marketed all-purpose hand soaps including liquid and lotion soaps, synthetic detergents, and antibacterial soaps containing PCMX and/or Triclosan. Bobrick soap dispensers are not designed to dispense alcohol-based hand sanitizers or iodine-based surgical soaps.

AUTOMATIC SOAP DISPENSERS, LIQUID AND FOAM



Automatic touch-free sensor eliminates cross contamination. Meets Barrier-Free accessibility standards. Sensor detects user's hand to automatically dispense controlled amount (0.8ml) of soap; activation range is 4" (100mm) from sensor lens. Reduces soap usage, waste. Bright-polished chrome spout cover.

Dispenses 1000 handwashes per 800ml, 2000 handwashes per 1600ml OneShot® soap refills. Soap refills available from sanitary supply distributors. Red LED light blinks when soap refill is low. Yellow LED light blinks when battery life is low (average battery life 90 soap refills or 2 years). Water-resistant battery compartment and motor housing.

Mounts through 1" (25mm) diameter hole in lavatory or countertop. Maximum countertop mounting thickness 2" (50mm). Spacer for use with lavatory rim 3/4" (19mm) or greater is included. Battery requirements: 4 Alkaline D Cells (not included).

B-826 AUTOMATIC, LAVATORY-MOUNTED LIQUID SOAP DISPENSER

B-826.18 Starter Kit Includes B-826 Automatic Lavatory-Mounted Liquid Soap Dispenser, an 800ml lotion soap refill, and 4 Alkaline D Cell batteries.

B-8263 AUTOMATIC, LAVATORY-MOUNTED FOAM SOAP DISPENSER

B-8263.18 Starter Kit Includes B-8263 Automatic Lavatory-Mounted Foam Soap Dispenser, an 800ml foam soap refill, and 4 Alkaline D Cell batteries.

826-20 AC ADAPTER (6V) for one B-826 or B-8263 Automatic Lavatory-Mounted Soap Dispenser.

Available on special order: All-metal soap dispenser for vandal-prone installations. AC Adapter (6V) for up to four B-826 or B-8263 Automatic Lavatory Mounted Soap Dispensers.

OneShot is a registered trademark of Rubbermaid Commercial Products.

B-822 SERIES DESIGNER'S NOTES:

1. Mount through 1" (25mm) diameter hole in lavatory or countertop.
2. Diameter of escutcheon: 2 1/16" (50mm).
3. Maximum height from base of body to bottom of container: 14 5/8" (370mm) for B-822, B-8226; 8 1/4" (210mm) for B-8221, B-82216. Allow clearance below basin for 3 1/2" (90mm) diameter container.
4. Mount with end of spout extending over inner edge of bowl.

B-826 AND B-8263 SERIES DESIGNER'S NOTES:

1. Maximum height from base of dispenser to bottom of refill 14 1/4" (360mm) for 800ml refill; 16 1/4" (415mm) for 1600ml refill.
2. Allow 5" (125mm) diameter clearance below lavatory or countertop for motor housing and 800ml refill. For 1600ml refill allow 5 1/2" (140mm) diameter clearance.
3. Battery compartment equipped with 36" (915mm) cord, mounts on wall under lavatory or countertop.