

## **Grab Bars**



#### **CONFIGURATIONS, DIMENSIONS, FINISHES:**

### 1 ½" (38MM) DIA. STRAÌGHT/SATIN

**B-6806x12"** (305mm) **B-6806x18"** (455mm) **B-6806x24"** (610mm) **B-6806x30''** (760mm) **B-6806x36"** (915mm) **B-6806x42''** (1065mm) **B-6806x48"** (1220mm)

#### 1 ½" (38MM) DIA. STRAIGHT/PEENED

**//B-6806.99x18''** (455mm) **#B-6806.99x24"** (610mm) **#B-6806.99x30"** (760mm) **#B-6806.99x36"** (915mm) **B-6806.99x42''** (1065mm)

#### 1 ¼" (32MM) DIA. STRAIGHT/SATIN

**B-5806x18''** (455mm) **B-5806x24"** (610mm (760mm) **B-5806x36''** (915mm) **B-5806x42"** (1065mm) **B-5806x48''** (1220mm)

#### 1 1/4" (32MM) DIA. STRAIGHT/PEENED

**B-5806.99x18''** (455mm) **#B-5806.99x24"** (610mm) **#B-5806.99x30"** (760mm) **#B-5806.99x36"** (915mm) **B-5806.99x42''** (1065mm)

#### **CONCEALED MOUNTING WITH SNAP FLANGE**

- Constructed of 18-gauge (1.2mm), type 304 satin-finish stainless steel tubing in 1 1/4" and  $1\frac{1}{2}$ " (32 and 38mm) diameters.
- Concealed mounting flange 1/8" (3mm) thick, type 304 stainless steel plate, 2" W x  $3\frac{1}{8}$ " H (50 x 80mm), with screw holes for concealed anchors.
- Cover is 22-gauge (0.8mm), type 304 stainless steel with satin finish, 3 1/4" (85mm) diameter.
- Cover snaps over mounting flange to conceal screws.

• Peened nonslip gripping surface available.

SERIES	DIAMETER	FINISH*
B-6806*	1 ½" (38mm)	Satin Finish
B-5806*	1 ¼" (32mm)	Satin Finish


\*Peened nonslip gripping surface available. Add suffix .99 to model number.

#### **OPTIONAL MOUNTING KITS**

Order one per flange. Part No. **252-30** (3) sheet-metal screws; 2521-30 (3) machine screws with toggle nuts; 2522-30 (3) machine screws with expansion shields.

#### **OPTIONAL ANCHOR DEVICES**

Order one per flange. Part No. **2583** anchors for  $\frac{3}{4}$ " to 1" (19–25mm) panels; **2586** anchors for  $\frac{1}{2}$ " (13mm) panels.



#### **#251-4** WingIt™ GRAB BAR FASTENER

For  $2\frac{1}{2}$ " and  $3\frac{1}{2}$ " (65 and 90mm) or deeper hollow walls with finished wall surfaces  $\frac{1}{4}$ " to  $\frac{1}{2}$ " (6 to 38mm) thick. One fastener required for each flange. Corrosion-resistant stainless steel. Install grab bars without backing. The fastener will support 300 lbs (136 kg) load. Patented. Winglt™ is a trademark of Winglt Innovations, LLC.

#### TWO-WALL TUB/ SHOWER TOILET COMPT.

24" W x 36" D (61 x 91cm)

1 ½" (38mm) Dia.

**B-68616** Satin

**B-68616.99** Peened

1 1/4" (32mm) Dia.

**B-58616** Satin

B-58616.99 Peened

# **TWO-WALL SHOWER**

15 7/8" W x 30 7/8" D (40 x 78cm)

1 ½" (38mm) Dia.

**₽B-6861** Satin

**B-6861.99** Peened



29" (74cm) Patented

1 <sup>1</sup>/<sub>4</sub>" (32mm) Dia.

**B-4998** Satin

**B-4998.99** Peened

#### TWO-WALL TUB/ **SHOWER TOILET** COMPT.

36" W x 54" D (91 x 137cm)

1 ½" (38mm) Dia.

**B-68137** Satin

**B-68137.99** Peened

1 <sup>1</sup>/<sub>4</sub>" (32mm) Dia.

**B-5837** Satin

**B-5837.99** Peened

#### TWO-WALL TOILET COMPT.

42" W x 54" D (107 x 137 cm)

1 ½" (38mm) Dia.

**B-6897** Satin

**B-6897.99** Peened

1 <sup>1</sup>/<sub>4</sub>" (32mm) Dia. **B-5897** Satin

**B-5897.99** Peened







#### SPECIAL GAMCO GRAB BARS WITHOUT THE SPECIAL ORDER

- Customized configurations and dimensions.
- Runs of one to thousands.
- · Brass and bronze metallic finishes.
- · Electrostatic precise color matching.





31