# CALRAD

# 20 Series - In-Wall Speakers

#### 20-330, 20-335 & 20-337

#### 2-WAY FLUSH-MOUNT, IN-WALL SPEAKERS

Manufactured specifically for the demand of the HiFi sound enthusiast, our 3 Flush-Mount Speaker Systems are designed for easy installation in walls or ceilings where conventional box speakers are undesirable. Now you can enjoy incredible sound in any room of your home or office, without need of additional floor or shelf space. Finished in white, they can be painted to blend with any wall color.

# Sold in pairs, packaged in separate boxes.

#### Specifications for 20-330:

Noofer	51/4" Poly	propylene Cone
Tweeter		
Crossover Freque	ncy	3 KHz
Frequency Respon	nse	50 Hz-20 KHz

#### Specifications for 20-335:

Woofer	6" Polypropylene Cone
Tweeter	1" Soft Dome
Crossover Frequency	2.5 KHz
Frequency Response	40 Hz-20 KHz


#### Specifications for 20-337:

Woofer	8" Polypropylene Cone
	1" Soft Dome
Crossover Frequency	2.5 KHz
Frequency Response	30 Hz-20 KHz

Wattage	. 35 + 35 watts, peak
Impedance	indicated on speaker
	7 <sup>1</sup> /2" x 11"
Cut-out Dimensions.	6 <sup>1</sup> / <sub>4</sub> " x 9 <sup>3</sup> / <sub>4</sub> "

Wattage		
Impedance	indicated	on speaker
Over-all Dimensions		8 <sup>5</sup> /8" x 12"
Cut-out Dimensions.		7 <sup>1</sup> /2" x 11"

Wattage	60 + 60 watts, peak
Impedance	8Ω
Over-all Dimensions	14 1/8" x 10 3/64"
Cut-out Dimensions	12 <sup>3</sup> /4" x 8 <sup>9</sup> /16"



#### 20-331

# 8 INCH ROUND FLUSH MOUNT CEILING SPEAKER

Features a mylar dome tweeter for outstanding performance. Easily mounts in walls and ceilings with built in retaining clips that automatically adjust to wall thickness. White finish. Attractive fine mesh grill. Wide frequency Response.

#### Specifications:

Sensitivity: 90 dB

Woofer: 8" (207mm) Polypropylene Cone Tweeter: 9/16" (13mm) Mylar cone

Depth: 3 1/2" (90mm) Grill width: 10 1/2" (270mm)

Frequency Response 50Hz -20KHz Wattage: 60 Watt RMS



## SPEAKER BRACKETS

**20-262-BK** Black **20-262-W** White

## **2 PIECES PER BOX**

Completely adjustable ABS plastic brackets are weather resistant and come complete with hardware and safety cable. Maximum load is 16 lbs.. Overall Height of 6.75". Rotation angle of 360° and a pivot angle of 40-90°. Specify black or white when ordering.

