



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



FIRE RATED for Drywall - Insulated FW-5050-DW

Application

- For drywall, walls and ceilings with galvanized steel drywall taping bead flange. For when temperature rise or heat transmission is a factor.

Product Features

- Insulated door panel • Concealed hinge • Self-Latching • Inside latch release
- Drywall taping bead flange • Self-closing

FW-5050 Access Door Specifications:

Door / Door Frame: Steel or Stainless Steel: 20 gage door, 16 gage mounting frame
Door filled with 2" thick fire rated insulation, flange to be drywall taping bead flange

Hinge: Concealed

Fire Rating (Walls): UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label.

Max size: 36 x 48. (Ceilings): Warnock Hersey International 3 hour rated in a non-combustible ceiling. 1 hour rated in a combustibile ceiling. Max size: 24 x 36

Standard Latch: Universal self-latching bolt, operated by either a knurled knob or flush key. When master keying is required, doors can be prepared for mortise cylinder locks.

Finish: Steel: 5 stage iron phosphate preparation with prime coat of white baked-on enamel.
Stainless Steel: #4 satin polish



STANDARD SIZES (Special sizes available upon request)

| NOMINAL DOOR SIZE W X H | | WEIGHT PER DOOR | | |
|-------------------------|------------|-----------------|------|------|
| inches | mm | Latches | lbs. | kg. |
| 8 X 8 | 203 X 203 | 1 | 8 | 3.6 |
| 10 X 10 | 254 X 254 | 1 | 9 | 4.1 |
| 12 X 12 | 305 X 305 | 1 | 10 | 4.8 |
| 14 X 14 | 355 X 355 | 1 | 12 | 5.4 |
| 16 X 16 | 406 X 406 | 1 | 15 | 6.8 |
| 18 X 18 | 457 X 457 | 1 | 20 | 9.1 |
| 22 X 30 | 560 X 762 | 1 | 32 | 14.5 |
| 22 X 36 | 560 X 914 | 2 | 35 | 15.9 |
| 24 X 24 | 610 X 610 | 1 | 28 | 12.7 |
| 24 X 36 | 610 X 914 | 2 | 38 | 18.1 |
| 24 X 48 | 610 X 1220 | 2 | 48 | 21.3 |
| 30 X 30 | 762 X 762 | 2 | 38 | 18.1 |
| 36 X 36 | 914 X 914 | 2 | 54 | 24.5 |
| 36 X 48 | 914 X 1220 | 2 | 76 | 34.5 |

Non Rated for Ceilings

Wall or ceiling opening is W + 3/8" (9 mm)
For detailed specifications see submittal sheet

