



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



SECURITY DOORS for Medium Security MS-7000

Application

- For use in medium security jails, prisons, psychiatric institutions, etc.
- Medium duty security access door

Product Features

- Door panel features rounded safety corners
- A one piece trim flange and continuous concealed hinge
- 12 Gauge door and frame

MS-7000 Access Door Specifications:

Door / Door Frame: Steel or Stainless Steel, 12 gauge door, 12 gauge mounting frame, Flush to frame with rounded safety corners and reinforced panel. One piece outer flange welded to mounting frame

Hinge: Continuous, concealed

Standard Latch: Tamper resistant allen head cam latch with security pin

Optional Latches/Locks: Spanner head cam latch, cylinder lock & key.

When master keying is required, doors can be prepared for rim or mortise cylinder locks

Finish: 5 stage iron phosphate preparation with prime coat of White alkyd baked-on enamel. Stainless Steel: Type 304 — #4 satin polish.



STANDARD SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
12 X 12	305 X 305	14	6.4
16 X 16	406 X 406	20	9.1
18 X 18	457 X 457	26	11.8
24 X 24	610 X 610	34	15.4
24 X 36	610 X 914	55	25
36 X 36	914 X 914	80	36.4

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

