

# CALRAD

## 30 Series - Connectors



**30-517**  
Isolated plastic Female XLR with protective cover. 3-pin Female XLR mounts in  $15/16$ " hole and requires a special cut out in order to mount.



**30-522-SL-4** 4 Pin Silver Male  
**30-522-SL-5** 5 Pin XLR chassis plug mounts in  $.75$ " hole size.



**30-523-SL-4** 4 pin Silver  
**30-523-BK-4** 4 Pin Black  
**30-523-SL-5** 5 pin Silver  
4 or 5 pin Female XLR chassis jack mounts in  $15/16$ " hole size.



**30-638**  
3-Pin XLR inline Female with labeled on/off switch. Shorts pins 2 & 3 to mute signal voltage with plastic noiseless switch. Gold plated contacts.



**30-514-BK**  
 $1/2$ " plastic XLR housing. Accepts all Calrad  $1/2$ " 'D' cut chassis mount connectors.




**30-590** Chrome  
**30-590-BK** Black Female XLR desktop mount in, used for quick release style gooseneck mics. Removable solder type Female XLR. Mounts with 3 screws included. Base dia.  $1.75$ ", height  $2$ ".



**30-524**  
XLR 3 pin Male to Male coupler.



**30-525**  
XLR 3 pin Female to Female coupler.



**30-595**  
Single XLR Female jack on a steel plate.  
**30-596**  
Dual XLR Female jacks on a steel plate.



**30-622-COLOR**  
Colored strain reliefs for 30-620 and 30-621. Specify color when ordering. Available in black, blue, green, orange, red and yellow.



**30-641-3** 3 pin  
**30-641-4** 4 pin  
**30-641-5** 5 pin  
**30-641-6** 6 pin  
Inline Female MINI XLR jack. Also available with short boot. Cable opening  $.13$ "- $.17$ "



**30-641M-3** 3 pin  
**30-641M-4** 4 pin  
**30-641M-5** 5 pin  
**30-641M-6** 6 pin  
Metal inline Female MINI XLR jack. Also available with short boot. Cable opening  $.13$ "- $.17$ ".




**30-640-3** 3 pin  
**30-640-4** 4 pin  
**30-640-5** 5 pin  
**30-640-6** 6 pin  
In line Male MINI XLR plug. Also available with short boot. Cable opening  $.17$ ".



**30-643-3** 3 pin  
**30-643-4** 4 pin  
**30-643-5** 5 pin  
**30-643-6** 6 pin  
Chassis mount MINI Female XLR. Mounts in  $15.20$ mm,  $.60$  hole. Nickel plated body.



**30-642-3** 3 pin  
**30-642-4** 4 pin  
**30-642-5** 5 pin  
**30-642-6** 6 pin  
Chassis mount MINI XLR Male. Mounts in  $.43$ " "D" hole. Nickel plated body.



**30-550** 9-way  
**30-551** 15-way  
**30-552** 25-way  
"D" solder type connector plugs



**30-560** 9-way  
**30-561** 15-way  
**30-562** 25-way  
"D" solder type connector sockets.



**30-553M** (Nickel)  
**30-553M-G** (Gold)  
DB9, DB15HD metal housing for 10-11mm cable, with hardware. 2-piece construction, for use with DB9, DB15 type connectors.



**30-554** (Male)  
**30-555** (Female)  
Solder type DB-9, 9 pin Male or Female with metal hood and hardware. Accepts cable up to 11mm,  $.433$ ".




**30-556** (Male)  
**30-557** (Female)  
Solder type HD-15, 15 pin Male or Female with metal hood and hardware. Accepts cable up to 11mm,  $.433$ ".



**30-553M-RA**  
Right angle version of 30-553M. for 10-11mm cable  
**30-553M-RA-G**  
Gold plated right angle hood and hardware.



**30-551-HD**  
DB-15 high density Male plug used for computer monitor applications, graphic workstations. Numbered pins. Gold plated terminals.



**30-561-HD**  
DB-15 high density Female jack used for computer monitor applications, graphic workstations. Numbered pins. Gold plated terminals.



**30-580**  
9-pin "D" connector plug to 9-pin "D" connector plug mini version.