



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



FIRE-RATED UNINSULATED

Recessed for drywall walls

FB-5015

Application

- For installation in drywall walls requiring concealing of the door panel consistent to surrounding walls
- Designed for openings that require a 1 1/2 hour fire rating when temperature rise is not a factor.

Product Features

- Recessed reinforced door fitted with 5/8" drywall.
- Concealed hinge, Self-closing, Self-latching
- Inside latch release
- Frame flange with pre-punched holes and textured for convenient mounting and accepting skim coat finish.

FB-5015 Access Door Specifications:

Door: Steel-22 Gauge recessed fitted with 5/8" thick drywall suitable to accept skim coat finish on site

Door Frame: Steel-22 Gauge press bent for strength and rigidity with pre-punched flanges for convenient mounting and accepting skim coat finish on site

Hinge: Concealed

Fire Rating (Walls): Meets 1 1/2 hour fire rating requirement in accordance with Underwriters Laboratories UL 10(b) and CAN/ULC S104-10 for max size upto 24" x 36"

Latch: Self-latching bolt, operated by flush key

Finish: Satin coat steel



Drywall insert included

AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
12 X 12	305 X 305	1	8.8	4
16 X 16	406 X 406	1	13	5.9
18 X 18	457 X 457	1	15.4	7
24 X 24	610 X 610	1	23.6	10.7
24 X 36	610 X 914	2	32.9	14.9

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

