

CALRAD

30 Series - Connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-414 Mono
30-417 Stereo
Metal 3.5 mm mono inline Female Audio Jack .16" cable opening with strain relief.



30-487 Stereo
30-487A Mono
Mini inline 3.5 mm mono or stereo Audio Jack, plastic handle w/strain relief. .19" cable opening.



30-492
Mini 3 circuit shielded stereo Audio Jack. 3.5 mm inline black metal finish and strain relief. .14" cable opening.



30-319F
Professional quality 3.5mm stereo inline Audio Jack with strain relief .26" cable opening. Mates with Calrad Male 3.5mm connector 30-319.



30-705
Inline Female 4 conductor 3.5mm Audio & Video Jack. Tip, ring 1, ring 2, sleeve. Plastic shell with strain relief. Mates to 30-700A, 30-701, and 30-702 plugs.



30-295 Nickel
30-295G Gold
3.5mm stereo Female to Female bulk head feed-thru Audio or infrared signal Jack. Mounts in 1/2" or 3/8" hole. Overall length 1.43". Available in gold or nickel.

30-295-1/2
1/2" Nickel Version.



30-295-HEX
3.5mm stereo feedthru with two Female to Female jack, 3/8" hex nut for panel mounting. Threaded body.



30-701 plastic
30-701A all metal
4 conductor 3.5mm Audio & Video Plug. Tip, ring 1, ring 2, sleeve, with strain relief. Cable opening .15".



30-706
4 conductor 2.5mm right angle Audio & Video Plug. Tip, ring 1, ring 2, sleeve. Cable opening .1".



30-702
4 conductor 3.5mm right angle Audio & Video Plug. Tip, ring 1, ring 2, sleeve. Cable opening .14".



30-707
4 conductor metal 3.5mm Female to Female Ground isolated feed-thru jack Mounts in 1/2inch opening.



30-485 Stereo
30-485A Mono
2.5 mm stereo or mono Audio Plugs with strain relief and metal housing. .13" cable opening.



30-423A
2.5 mm sub-mini Audio Plug with plastic grip, 2 cond. Improved solder points. 7/16" plug length. .15" cable opening.



30-376-2.5 Mono
30-386-2.5 Stereo
2.5 mm right angle stereo or mono Audio Plugs. .15" cable opening.



30-479
2.5mm inline stereo Audio Jack with strain relief .13" cable opening. Plastic non conductive insert.



30-493A, 3.5mm
30-494A, 2.5mm
Mini or sub mini stereo Audio Jack. Panel mount. Mounts in .25 hole. Bushing length .165".



30-700A
4 conductor 3.5mm chassis mount stereo Audio & Video Jack. Tip, ring 1, ring 2, sleeve. Mounts in .28" hole.



30-712K-S
Solderless Keystone & Chassis Mount 3.5mm stereo Jack. 1/2" chassis mount or keystone insert. Screw terminals provide a clean solderless termination. 18 to 30 gauge wire.

Small Slotted Screw Driver Required



30-712K-S-2
2.5mm stereo version

3.5mm VERSION
30-710 2 conductor
30-711 3 conductor
30-712 4 conductor
2.5mm VERSION
30-713 2 conductor
30-714 3 conductor
30-715 4 conductor



Non-Conductive Housing

3.5mm or 2.5mm snap-in chassis mount Audio Jack. Nickel plated connector with black molded trim. Isolated from ground, requires no hardware, solder style terminals. Mounts in .375" hole up to .07" panel thickness.

30-493A-6 inch
3.5mm Mini stereo audio jack with 6 inches stripped and tinned leads. Shielded two conductor cable with Black shrink tube strain relief. Red and Black wire color. Mounts in 1/4 hole. .165" bushing length.

