



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



# RECESSED Drywall Panel Door DW-5058

## Application

- Designed to provide access in walls and ceilings, while maintaining an invisible, architecturally pleasing appearance

## Product Features

- Designed to accommodate 5/8" drywall, the frame can be reversed to accommodate 1/2" drywall
- Standard with a touch latch feature

## DW-5058 Access Door Specifications:

**Door:** .080 aluminum extrusion with 5/8" drywall inserted into door panel

**Door Frame:** .080 aluminum extrusion recessed to provide similar edge to drywall bead to allow for finishing of wall or ceiling surface.

**Hinge:** Spring loaded hinge pin allows door panel to open to 90 degrees, and also allows for door panel to be removed from frame. Safety chain installed on door & frame for safety.

**Standard Latch:** Concealed Touch Latches

**Optional Latches/Locks:** Screwdriver operated cam latch, allen head cam latch, spanner head cam latch, cylinder lock & key.

**Finish:** Mill Finish. Drywall is ready to be finished to match surrounding wall or ceiling surface.



## AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
12 X 12	305 X 305	2.0	0.9
16 X 16	406 X 406	5.0	2.3
18 X 18	457 X 457	6.0	2.7
24 X 24	610 X 610	12.0	5.5
24 X 36	610 X 914	21.0	9.5

Wall or ceiling opening is W + 1/2" ( 12 mm)  
For detailed specifications see submittal sheet

