


### SUB-MINIATURE VOLUME CONTROLS

Linear taper, extremely smooth for quiet operation. 1/2" dia. fits into 1/4" hole. Shaft 3/16" dia. Thread length 7/32", shaft length 9/16", 1 1/8" length overall. Supplied with mounting hardware. Specify resistance. .1watt, 20% tolerance, 300° rotation. (One per package.) Solderable terminals.

*25-290	.....	2KΩ Linear Taper
*25-294	.....	100KΩ Linear Taper
*25-295	.....	250KΩ Linear Taper



### VOLUME CONTROL LESS SWITCH

Replacement controls available in the eight most popular values. High quality carbon elements which have high stability under most conditions. 15/16" dia., 1/2" deep, 1/4" dia. shaft, 1/4" thread length, 5/16" shaft length, 5/16", bushing, fits in 3/8" hole. 25-324 Long shaft 2" bushing. 1/2 watt, 20% tolerance, 320° rotation. Supplied with hardware. Solderable terminals.

*25-324	Long Shaft.....	2KΩ Linear Taper	*25-328	.....	100KΩ Linear Taper
*25-325	.....	5KΩ Linear Taper	*25-329	.....	250KΩ Linear Taper
*25-326	.....	10KΩ Linear Taper	*25-330	.....	500KΩ Audio Taper
*25-327	.....	50KΩ Linear Taper	*25-331	.....	1 MΩ Audio Taper



### MINIATURE CONTROLS WITH SWITCH

Designed to provide extremely smooth quiet operation. Semi-log (audio) taper. Fits 5/16" hole in panels, 1/4" shaft, 13/16" long, including threads, size 5/8" dia., 1 9/16" long. Specify resistance. 1/2 watt, 20% tolerance, 300° rotation. SPST switch. Switch current 125v @ 3 amps.

*25-316	.....	5KΩ Audio Taper	*25-318	.....	50KΩ Audio Taper
*25-317	.....	10KΩ Audio Taper	*25-322	.....	1 MΩ Audio Taper



### MINIATURE VOLUME CONTROLS

Replacement control less switch 5/8" dia, fits 9/32" hole. Shaft 1/4" dia., 9/16" long including thread. Supplied with mounting hardware. Specify resistance. 1/4 watt, 20% tolerance, 300° rotation. Solderable terminals.

*25-300	.....	2KΩ Linear Taper	*25-305	.....	250KΩ Linear Taper
25-300A	.....	1KΩ Linear Taper	*25-306	.....	500KΩ Audio Taper
25-301	.....	5KΩ Linear Taper	*25-307	.....	1 MΩ Audio Taper
25-302	.....	10KΩ Linear Taper	*25-308	.....	10KΩ Audio Taper
*25-303	.....	50KΩ Linear Taper	*25-309	.....	50KΩ Audio Taper
*25-304	.....	100KΩ Linear Taper	*25-310	.....	100KΩ Audio Taper



### MINIATURE DUAL VOLUME CONTROLS

Extremely smooth action control with 11/16" dia., fits into 9/32" hole. Extra long thread 9/16", shaft 1/4" dia. Circuit board mounting tabs. Shaft length 1/2". 1/4 watt, 20% tolerance, 300° rotation. 1" overall length. Solderable terminals.

25-395	.....	5KΩ Audio Taper	*25-397	.....	50KΩ Audio Taper
25-396	.....	10KΩ Audio Taper	*25-398	.....	100KΩ Linear Taper (.01 watt)



### MINIATURE MULTI-CLICK RATCHET CONTROLS-P.C. MOUNT 10 step

11/16" dia. body, 1/4" dia. shaft, 9/16" shaft length, including threads, fits into 9/32" hole. 7/8" long overall. 1/4 watt, 20% tolerance, 300° rotation. Solderable terminals.

25-420	.....	5KΩ Linear Taper (.1 watt)	*25-428	.....	5KΩ Audio Taper
25-421	.....	10KΩ Linear Taper (.1 watt)	*25-429	.....	10KΩ Audio Taper
*25-422	.....	50KΩ Linear Taper	*25-430	.....	50KΩ Audio Taper
25-423	.....	100KΩ Linear Taper	*25-431	.....	100KΩ Audio Taper
25-424	.....	250KΩ Linear Taper	*25-432	.....	250KΩ Audio Taper
			*25-433	.....	500KΩ Audio Taper



### MINIATURE MULTI-CLICK DUAL CONTROLS—40 STEP P.C. MOUNT

11/16" dia., 1 1/4" long overall, 9/32" hole size, 1/4" dia shaft, 9/16" long shaft including threads. 1/4 watt, 20% tolerance, 300° rotation. Solderable terminals.

*25-405	.....	10KΩ Linear Taper	*25-410	.....	10KΩ Audio Taper
*25-406	.....	50KΩ Linear Taper	*25-411	.....	50KΩ Audio Taper
25-407	.....	100KΩ Linear Taper	*25-412	.....	100KΩ Audio Taper



POTENTIOMETERS WITH AN \*ASTERISK\* NEXT TO THE PART NUMBER ARE BY SPECIAL ORDER ONLY, PLEASE CONTACT CALRAD FOR ORDERING REQUIREMENTS 323-465-2131