

CALRAD

30 Series - Connectors



30-310 2.1mm
30-311 2.5mm.
Chassis mount coax power jack. Insulated housing mounts in $\frac{5}{16}$ " hole. N/C switch. 5.5mm O.D.



30-355
Right angle coax power plug. .3mm I.D., 3.5mm O.D. with solder terminals. .22" x .12" cable opening.



30-356
Right angle coax power plug. 2.1mm I.D., 5.5mm O.D. with solder terminals. .22" x .12" cable opening.



30-357
Right angle coax power plug. 2.5mm I.D., 5.5mm O.D. with solder terminals. .22" x .12" cable opening.



30-377 Japan
30-377-T Taiwan
2.1mm I.D.
5.5mm O.D.
chassis mount coax power jack. Mounts $\frac{7}{16}$ " dia. hole in panels up to $\frac{3}{16}$ " thick.



30-378 Japan
30-378-T Taiwan
2.5mm I.D.
5.5mm O.D.
chassis mount coax power jack. For $\frac{7}{16}$ " dia. hole in panels up to $\frac{3}{16}$ " thick.



30-379
3.0mm I.D.
6.3mm O.D.
chassis mount coax power jack. For $\frac{7}{16}$ " dia. hole in panels up to $\frac{3}{16}$ " thick.



30-340
Coax power plug converter. 1.3 mm plug to 2.1 mm jack.
30-341
2.5 mm jack version



30-343
Coax power plug converter. 2.5mm plug to 2.1 mm jack
30-344
2.5 mm jack version



30-348
Power plug converter 3.5mm plug to 2.1mm jack.



30-346
Coax power plug converter. 3.5mm plug to 2.1mm jack
30-347
2.5 mm jack version



3.5 mm mono mini-jack to DC power plug.
30-360
1.3mm coax plug I.D.
30-361
2.1mm coax plug I.D.
30-362
2.5mm coax plug I.D.



30-349
Power plug converter 3.5mm plug to 2.5mm jack.



30-363
3.5 mm mini-jack to DC power plug.
3.0 mm coax plug I.D.



30-721
Sony DC power plug with plastic strain relief. 6mm O.D. Center pin 1.3mm 1.97" overall length. accepts .17" cable O.D.



30-602-BK Black
30-602-RD Red
Banana plug, solderless with gold plating, screw adjustment with black or red band. .15" cable opening.



30-605-BK Black
30-605-RD Red
Solder type banana plug for large cable. Gold plated with black or red bands. Up to 8 awg wire. .25" cable opening.



30-603
Locking banana plug, can be locked down in jack, solderless, gold plated. .34" cable opening.



30-442 Black
30-443 Red
Insulated banana plug, 1" molded bakelite handle, .2" cable opening.



30-442G Black
30-443G Red
Gold versions of 30-442 and 30-443. .2" cable opening.



30-600-BK Black
30-600-RD Red
Banana plug, gold plated solderless with Female banana tap. Black or red. .22" cable opening.



30-600-RB-BK
30-600-RB-RD
Gold plated with rubber body. Has 2 set screws to hold cable. Fits standard banana jack.



30-604-BK Black
30-604-RD Red
Dual gold banana plugs. For up to 8 gauge wire. .15" cable opening. 0.75" centers.



30-604-CT-BK
30-604-CT-RD
Dual gold banana plugs with flexible body. For up to 8 gauge wire. .15" cable opening. 0.75" centers.