# CALRAD

## 40 Series - VGA, HDMI, Component Video Converters/Scalers

#### **40-281H COMPONENT VIDEO TO HDMI CONVERTER**

Convert Y, Pb, Pr component video and analog or digital audio to HDMI 1.2 or DVI 1.0. Supports 480I, 480P, 720P, 1080I and 1080P. The 40-281H has RCA jacks for Component video inputs, PCM digital audio and 3.5 mm stereo audio. The audio input select switch allows you to switch between analog or digital audio in. 5 Volt DC power supply included.

#### Specifications:

Input Component video,  $3 \times RCA$  jacks for Y, Pb, Pr  $1 \times 3.5 mm$  stereo jack for analog audio,  $1 \times RCA$  jack for PCM digital audio Output: One HDMI Female port.

Dimensions: Length 4.2" X Width 3.0" X Height 1.2"

Power: 5 Volt DC



The 40-283HD allows you to switch between two HDMI 1.2 inputs and convert them to component video (Y, Pb, Pr) and analog or digital audio out. Supports 480I, 480P, 720P, 1080I and 1080P resolutions. IR remote control is used for power on/off and selecting between the 2 HDMI inputs. If the HDMI 1.2 inputs are HDCP encrypted the component video output will be turned off. 5Volt DC power supply included.

#### Specifications:

Output: Three RCA jacks for Y, Pb, Pr. One 3.5mm stereo jack for analog audio. One RCA jack for PCM digital audio Outputt: Two HDMI Female ports. Dimensions: Length 4.2" X Width 4.0" X Depth 1.2", Power: 5Volt DC

## 40-480 VGA TO COMPONENT VIDEO CONVERTER WITH OSD (ON SCREEN DISPLAY) SETUP MENU

Converts VGA to component video (Y, Pb, Pr). VGA to Converter Box can convert XGA (VGA /SVGA/XGA /SXGA) to YpbPr video, allowing connection of PC based devices for viewing on high-definition component video displays. This converter box provides you with a economic, high-efficient and perfect video converter solution. Settings include brightness, contrast, color saturation and hue. Select 4:3, 16:9 or full screen display modes. Both PC and MAC Computer are supported. Standard resolutions are 480I, 576I, 480P, 576P, 720P, 1080I. Size: Length 5" x Width 3.7" x Height 1.33".Includes 5Vdc, 1Amp power supply, 3 ft. VGA and component video cables.

### 40-481 COMPONENT TO VGA VIDEO CONVERTER WITH OSD (ON SCREEN DISPLAY) SETUP MENU


Converts component video (Y, Pb, Pr) to VGA video. YpbPr Video to VGA Converter Box can convert YpbPr video to XGA (VGA /SVGA/XGA /SXGA), allowing connection of PS2, PS3, Xbox, Xbox360, Wii, Game Cube, CRT or LCD, Apple TV, Vudu Box, or Netflix Roku Player to a computer monitor, projector, or other display that supports VGA, and allowing viewing high-definition DVD and picture on PC. This converter box provides you with a economic, high-efficient and perfect video converter solution. Settings include brightness, contrast, color saturation and hue. Select 4:3, 16:9 or full screen display modes. Both PC and MAC Computer are supported. Standard resolutions are 480I, 576I, 480P, 576P, 720P, 1080I. Size: Length 5" x Width 3.7" x Height 1.33". Includes 5Vdc, 1Amp power supply. Includes 3 ft. M-M component video and M-M audio cables.














OSD Menu DC Power VGA
Buttons Jack In/Out

