



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



SPECIALTY DOORS

Surface Mounted

SF-2000

Application

- An innovative surface mounted access door for all types of walls and ceilings

Product Features

- An exposed continuous piano hinge allows the door panel to open to 175 degrees
- There is no frame to extend into the wall or ceiling
- Perfect for access to odd size openings

SF-2000 Access Door Specifications:

Door / Door Frame: Steel: 16 gage, flush to frame with rounded safety corners and a one piece outer flange
Frame is one piece outer flange

Hinge: Exposed continuous piano hinge

Standard Latch: Stainless steel screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock & key, allen head cam latch, spanner head cam latch

Finish: 5 stage iron phosphate preparation with White alkyd baked-on enamel



STANDARD SIZES (Special sizes available upon request)

| NOMINAL DOOR SIZE W X H | | WEIGHT PER DOOR | | |
|-------------------------|-----------|-----------------|------|-----|
| inches | mm | Latches | lbs. | kg. |
| 8 X 8 | 203 X 203 | 1 | 2 | 0.9 |
| 12 X 12 | 305 X 305 | 1 | 4 | 1.8 |
| 16 X 16 | 406 X 406 | 2 | 6 | 2.7 |
| 24 X 24 | 610 X 610 | 4 | 14 | 6.4 |

Wall & Ceiling opening is $W - 1/4"$ (7 mm)
For detailed specifications see submittal sheet

