# CALRAD

## 55 Series - Easy Install HDTV Cables

Technical drawings and specifications are available for these cables. Please ask your Calrad sales representative for details.

#### 350 MHz EZ-HDTV / VGA CABLES

Installing a 15 pin HDTV cable in a wall or conduit just became much easier. No more on-site cable prep or connector soldering. Just snake and plug, it's that EZ.

### Supports PC Plug and Play Male HD-DB15 Female HD-DB15 Easy grip thumb screws with stainless steel slotted screwdriver tips Ferrite Core for reduction of RFI, EMI interference 85% braided, tin plated overall shield with 5 miniature shielded coax Male 8 Pin cables Mini-Din .46 Inch Diameter Protective pin cap to Female 8 Pin Mini-Din cover mini-din

ALL PIGTAILS SOLD SEPARATELY

No heat shrink here, solid molded strain relief for strong cable termination



connector when

fishing the cable

This Keystone feed-thru jack can be used to pass HDTV, SVGA etc. through a decora wall plate using a single keystone port. Calrad part number 72-304-8-COLOR, Red, Black, White, Ivory, Green, Blue, Yellow, Orange or Purple color options available. Requires one 55-614-EI-Length-PP and one 55-614-EI-12-PP cable to work







55-614-EI-HD15P Male HD-DB15 to 8 Pin Female Mini Din



55-614-EI-RCAPP 5 RCA Molded Males to 8 Pin Female Mini Din



55-614-EI-BNCPP 5 BNC Molded Males to 8 Pin Female Mini Din



Use Calrad 30-588 gender changer to convert the Female HD-DB15 connector on the 55-614-EI-PP cable to a Male HD-DB15. (not included)

#### **NEW PLUG N PLAY DESIGN EASY INSTALL CABLE**

Engineered for video excellence. Our easy install (EI) cables are suitable for passing the cable through ½" conduit or similar small openings. The specifications of this cable are ideal for critical or long runs, even with HDTV signals. Perfect for HDTV, Home Theater PCs, Video Amplifiers, Scalers and any situation where signal quality should not be compromised. This cable enables your equipment to reproduce the best color saturation,

black level, and picture detail possible. Our cable construction features five tin-plated, individually shielded 75 ohm mini coax cables. This design insures the critical horizontal and vertical sync timing signals accurately pass from one end of the cable to the other. Since the signal is split into red. green and blue primary colors and then reassembled, the signals must arrive at the same time at the destination. The more the timing variance, the less detail can be resolved in the resulting picture. Calrad guarantees a maximum timing variance of 3 nanoseconds per 100 feet of cable. Our high quality HD-DB15 and 8 pin mini din connectors provide solid low resistance pin-pin signal path terminations. Male to Male and Male to Female plus RCA and BNC versions available.

Lengths Available	
55-614-EI-12-PP	12 ft.
55-614-EI-15-PP	15 ft.
55-614-EI-25-PP	25 ft.
55-614-EI-35-PP	35 ft.
55-614-EI-50-PP	50 ft.
55-614-EI-75-PP	75 ft.
55-614-EI-100-PP	100 ft.

#### RCA, BNC OR VGA PIGTAIL ADAPTERS

Need something besides VGA Male to Female. Adapt your cable to fit your needs with one of three alternative pigtail ends. Available in either VGA , RCA or BNC Male configurations, these pigtails give our 55-614-EI-PP the adaptablity needed in todays complex audio & video market. All adapters are 1 foot in length with molded ends. Adapters sold separately