

CALRAD

55 Series - RF Cables

COAX JUMPER CABLES

RG59U or RG6 coax cable with molded Male "F" connectors each end.



Shielding specifications

for RG6 cables:

Conductor: 1.1mm copper
 Insulation: 5.0mm foam PE
 Brading 60%: 32 x 0.12mm CU
 Foil 100%: 0.025mm
 O.D. PVC: 6.8mm
 UL Approved.

RG6	
55-790	3 ft., Black
55-790-W	3 ft., White
55-791	6 ft., Black
55-791-W	6 ft., White
55-792	12 ft., Black
55-792-W	12 ft., White
55-793	15 ft., Black
55-793-W	15 ft., White
55-794	25 ft., Black
55-794-W	25 ft., White
55-795	50 ft., Black
55-795-W	50 ft., White
55-796	75 ft., Black
55-796-W	75 ft., White
55-797	100 ft., Black
55-797-W	100 ft., White

RG59

55-882-1	1 ft., Black
55-882-2	2 ft., Black
55-882	3 ft., Black
55-882-W	3 ft., White
55-883	6 ft., Black
55-883-W	6 ft., White
55-884	12 ft., Black
55-884-W	12 ft., White
55-885	25 ft., Black
55-885-W	25 ft., White
55-886	50 ft., Black
55-886-W	50 ft., White
55-888	75 ft., Black
55-888-W	75 ft., White
55-887	100 ft., Black
55-887-W	100 ft., White



These cables are available in UL approved versions. Ask your Calrad sales representative for details.

RG6 COAX JUMPER CABLES WITH PERMA-SEAL COMPRESSION "F" CONNECTORS

UL Black RG6 cable with 1.1mm center conductor. 60% tin plated braid and 100% foil shielding. These come with weather resistant Perma-Seal style compression connectors.

55-790-PS-BK	3 ft. Black
55-790-PS-WH	3 ft. White
55-791-PS-BK	6 ft. Black
55-791-PS-WH	6 ft. White
55-792-PS-BK	12 ft. Black
55-792-PS-WH	12 ft. White
55-793-PS-BK	15 ft. Black
55-793-PS-WH	15 ft. White
55-794-PS-BK	25 ft. Black
55-794-PS-WH	25 ft. White
55-795-PS-BK	50 ft. Black
55-795-PS-WH	50 ft. White
55-796-PS-BK	75 ft. Black
55-796-PS-WH	75 ft. White
55-797-PS-BK	100 ft. Black
55-797-PS-WH	100 ft. White



55-650 RG-6 COAX & MESSENGER CABLE

UL 75 ohm, 18 awg copper covered steel, 0.109" galvanized steel messenger inner shield PP-aluminum laminated overlapped tape bonded to dielectric, 67% tinned copper braid. 0.193" nom O.D. CPE dielectric, 0.275" nom O.D. black PVC jacket. UL AWM style 1354, 80° 300V. SLR 20dB min at 5-1000MHz. Meets NEC 820-V rating min. Color: black.

55-650-25	25 ft.
55-650-50	50 ft.
55-650-75	75 ft.
55-650-100	100 ft.
55-650-150	150 ft.



55-798

FLAT RG-6 CABLE

8" white, flat Female to Female "F" jumper cable. Thickness is $\frac{3}{32}$ ". Eliminates drilling through walls and conveniently runs under or over window and doors. Suitable for DBS installations in apartment buildings, cabins, motor homes and condominiums. Mounting adhesive-taped back. Nickel plated brass "F" connectors. Soft waterproof white PVC jacket. Size: .52" Width X .20" Thick



55-1050

SHIELDED CAMERA AV + POWER 20 METER EXTENSION CABLES 20 METERS

Provides video, audio, power signal thru one cable for Calrad or other video cameras. Used as a stand alone cable or to extend existing cables. Color coded cables, red=power, yellow = video, white=audio. Cable O.D. .217". Color is Off white.



55-1050-1

Audio/Video:.....Male to Male RCA connectors
 Power:.....Male to Female 2.1mm coax power connectors

55-1050-2

Audio/Video:.....Male to Female RCA connectors
 Power:.....Male to Female 2.1mm coax power connectors